SIEMENS

Data sheet 5SE2306

NEOZED fuse link 400 V gL/gG, Size D01, 6 A, Folding box with tin-coated contact caps



Model	
Product brand name	SENTRON
Product designation	NEOZED fuse link
Design of the product	With tin-coated contact caps
Product variations	Pack of 10
Design of the fuse link	NEOZED fuse link

General technical data	
Size of fuse system / acc. to DIN EN 60269-1	D01
Operating class of the fuse link	gG
Supply voltage	
• at AC / rated value	400 V
• at DC	250 V
Protection class IP	IP20, with connected conductors
Switching capacity current / acc. to IEC 60947-2 / rated value	50 kA

Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.4 W

Subject to change without notice
© Copyright Siemens

Current / at AC / rated value	6 A

Main circuit

Operating voltage / rated value	400 V
Operating current / rated value	6 A

Appearance

Color coding of the fuse link	Green
Maximum short-circuit current breaking capacity (Icu) / at AC / rated value	50 kA
Mounting position	Any, preferably vertical
Net weight	8 g
Ambient temperature	
• minimum	-5 °C
• maximum	40 °C
Environmental category	Up to 45°C at 95 % rel. humidity

Certificates

Reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval		Declaration of Conformity	Test Certificates		
ÖVE	VDE	EG-Konf.	Type Test Certificates/Test Report	Special Test Certificate	Miscellaneous

other

Environmental Confirmations

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2306


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5SE2306


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2306

CAx-Online-Generator
http://www.siemens.com/cax

Tender specifications
http://www.siemens.com/specifications

Subject to change without notice
© Copyright Siemens





Subject to change without notice
© Copyright Siemens