Single screw Terminal Blocks, ZJU-150 type: for wires 150 mm²

FEATURES & BENEFITS

- -
- -
- -



LOGISTIC DATA

Available packages	5
Weights	374.7

MECHANICAL DATA

A recommended tip screwdriver (hexagon)	8
Stripping length [mm]	35
Crimping shape	trapezoid
Max. tightening torque [Nm]	25
Cross-sections of cables (wire/ cord) [mm²]	35÷150 / 50÷150
Ambient temperature [°C]	-25 ÷ +55
Dimension [mm]	100 x 118,5 x 31,7
Type marker	EZU-10

ELECTRICAL DATA

Nominal cross-section [mm²]	150
Rated insulation voltage U_i [V]	1000
Constant current [A]	309
Electric durability [kV]	4

CERTIFICATES & STANDARDS

Level of security	IP00
Combustibility class	UL 94 V0
Standards	PN-EN 60947-7-1

Type	Index Ergom	Colour	Housing
ZJU-150	R34RR-07010000901	grey	polyamide
ZJU-150 (5 SZT./PCS)	R34RR-07010000903	grey	poliamid
ZJU-150/YL	R34RR-07010000911	yellow	polyamide
ZJU-150/YL (5 SZT./PCS)	R34RR-07010000913	yellow	poliamid
ZJU-150/BL	R34RR-07010000921	blue	polyamide
ZJU-150/BL (5 SZT./PCS)	R34RR-07010000923	blue	poliamid
ZJU-150/RD	R34RR-07010000931	red	polyamide
ZJU-150/RD (5 SZT./PCS)	R34RR-07010000933	red	poliamid
ZJU-150/BK	R34RR-07010000941	black	polyamide
ZJU-150/BK (5 SZT./PCS)	R34RR-07010000943	black	poliamid

Date of publication: 15/2/2018

Graphic project, pictures and all technical data and descriptions in this catalogue are protected by Polish and international copyright laws. Names and logos used in the content of this catalogue may be trademarks, for which ZAE Ergom Sp. z o.o. has exclusive protection rights. ZAE ERGOM reserves the right for changes in the assortment and parameters of its products.