Single screw Terminal Blocks ZJUN-50 type for wires 50 mm²

FEATURES & BENEFITS

- -
- -
- -



CE

MECHANICAL DATA

A recommended tip screwdriver (hexagon)	23
Stripping length [mm]	23
Crimping shape	trapezoid
Max. tightening torque [Nm]	10
Cross-sections of cables (wire/ cord) [mm²]	2,5÷50 / 6÷50
Dimension [mm]	51 x 43,5 x 18

ELECTRICAL DATA

Nominal cross-section [mm²]	50
Continuous current Al. [A]	145
Continuous current Cu [A]	160
Rated insulation voltage U_i [V]	750
Electric durability [kV]	3

CERTIFICATES & STANDARDS

Level of security	IP00
Combustibility class	UL 94 V0
Standards	PN-EN 60947-7-1

NOTE!

The assembly directly under module shields.

Type	Index Ergom	Colour	Housing	Available packages [szt.]	Weights [g]
ZJUN-50	R34RR-07010001701	grey	polyamide	1	34
ZJUN-50 (10 SZT./PCS)	R34RR-07010001703	grey	poliamid	10	340
ZJUN-50/BL	R34RR-07010002701	blue grey	polyamide	1	34
ZJUN-50/BL (10 SZT./PCS)	R34RR-07010002703	blue grey	poliamid	10	340
ZJUN-50 PE	R34RR-07020001701	yellow-green	polyamide	1	34
ZJUN-50 PE (10 SZT./PCS)	R34RR-07020001703	yellow-green	poliamid	10	340

Date of publication: 15/2/2018

Graphic project, pictures and all technical data and descriptions in this catalogue are protected by Polish and international copyright laws. Names and logos used in the content of this catalogue may be trademarks, for which ZAE Ergom Sp. z o.o. has exclusive protection rights. ZAE ERGOM reserves the right for changes in the assortment and parameters of its products.