

GES9-3B service outlet with handle clamp

Type	Colour	Pack. pcs	Weight kg/ 100 pcs.	Item No.
GES9-3B U 7011	Iron grey	1	205,000	**7405 07 7**
GES9-3B U 9011	Graphite black	1	205,000	**7405 07 9**
GES9-3B U 1019	Grey-beige	1	205,000	**7405 08 1**

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.






Service outlet with handle clamp for up to 12 individual Modul 45 devices in 3 UT4 universal supports, use in duct systems and system floors.
Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 10 mm.


Up to 9 installation devices with 50 mm central plate can be inserted.

GES9-3S service outlet with locking slider

Type	Colour	Pack. pcs	Weight kg/ 100 pcs.	Item No.
GES9-3S U 7011	Iron grey	1	199,500	**7405 08 3**
GES9-3S U 9011	Graphite black	1	199,500	**7405 08 5**
GES9-3S U 1019	Grey-beige	1	199,500	**7405 08 7**

PC/ABS Polycarbonate/Acrylonitrile-butadiene-styrene /pc.






Service outlet with locking slider for up to 12 individual Modul 45 devices in 3 UT4 universal supports, use in duct systems and system floors.
Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 10 mm.

Up to 9 installation devices with 50 mm central plate can be inserted.

GES9M-2 service outlet with handle clamp

Type	Material	Floor covering thickness mm	Pack. pcs	Weight kg/ 100 pcs.	Item No.
GES9M-2 10U	V2A	10	1	360,000	**7405 37 1**

V2A Stainless steel, grade 304 /pc.






Service outlet with handle clamp for up to 12 individual Modul 45 devices in 3 UT4 universal supports, use in duct systems and system floors.
Locking ladder made of galvanised sheet steel


Up to 9 installation devices with 50 mm central plate can be inserted.

ZES9 inspection cover

Type	Colour	Floor covering thickness mm	Pack. pcs	Weight kg/ 100 pcs.	Item No.
ZES9-2 U10T 7011	Iron grey	5	1	206,300	**7406 67 2**
ZES9-2 U10T 9011	Graphite black	5	1	206,300	**7406 67 4**
ZES9-2 U10T 1019	Grey-beige	5	1	206,300	**7406 67 6**

PA Polyamide /pc.





Junction box insert for blank closing of a square mounting opening of nominal size 9 in an underfloor duct or trunking system or in raised floor. Polyamide floor covering profile.
Recess is 5 mm, if necessary, adjustable to 3, 8 or 10 mm.

Always indicate the item number when ordering.