

202276EX

MIGNON-EX TWO-WAY SWITCH 1X16A 3D 3G

Registry	
Net weight	0,245
Min order quantity	1
EAN Code	8014950093731
Gross Weight	0,244

Reference Standards	Standards
EN 60079-0/A11: 2013	2011/65/UE
EN 60079-0: 2012	2012/19/UE
EN 60079-15: 2010	2014/34/EU
EN 60079-31: 2014	2014/35/EU
EN 60669-1/A1: 2002	
EN 60669-1/A2: 2008	
EN 60669-1/IS1: 2009	
EN 60669-1: 1999	

Marks

CE

Download EX Instructions / EU Conformity

Technical data	
Dimensions	62X108X48 mm
Hole type	M20
Number of entries in enclosure	1
Rated current/voltage	16A 250V~10A 400V~
Frequency	50/60Hz
Protection degree	IP66
Poles	1P
Nominal Operating Voltage	250V~/400V~
Manufacturing Material	Thermosetting halogen free
DEVICE FUNCTION	Two way switches
Width	62 mm
Nominal current	16/10A
Execution	WALL MOUNTING
Insulation Class	II

Atex	
ATEX application zone	Zona/Zone 2 and 22
Atex Dust Nominal Current	-
Atex Gas Nominal Current	-
Atex Dust Marking	Ex tc IIIC T70°C Dc
Atex Gas Marking	Ex nR IIC T6 Gc
GAS Dissipable Power	-
DUST Dissipable Power	-
Min. Amb. Temp.	-20°C
Max. Amb. Temp.	+40°C
Group & Cat. ATEX GAS	II 3G
Group & Cat. ATEX DUST	II 3D
Type istruction EX	10043.pdf

Attachments

DXF drawing