# CAMEA PRO LED EVO 10W MAT BIAŁA 4000K

BULKHEADS



220-240 V 50-60 Hz | LED | IP44 | IK10 | CE

## TECHNICAL PARAMETERS

| | |
|---|---|
| Index: | 206016/HV |
| Ingress protection: | IP44 |
| Impact resistance: | IK10 |
| Nominal power [W]: | 10 |
| Luminous flux [lm]*: | 1090 |
| Colour temperature [K]: | 4000 |
| Energy efficiency class: | A+ |
| Material of the body: | PP |
| Diffuser material: | PC |
| Diffuser type: | OPAL |

*Tolerance +/- 10%

## CHARACTERISTICS

Surface mounted round LED bulkhead with integrated, energy- saving light source LED GO!, high luminous flux and ingress protection class IP44 . Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10).

## APPLICATION

Surface mounted luminaire for ceiling or wall installation, dedicated for indoor use - in general utility rooms, passageways, staircases. Available option with a radio motion sensor (RCR), which is particularly recommended for use in public areas

# CAMEA PRO LED EVO 10W MAT BIAŁA 4000K

## BULKHEADS

LED GO!

## TECHNICAL PARAMETERS TABLE

| | | | |
|---|---|---|---|
| Light source: | LED GO! | Material of the body: | PP |
| Nominal power [W]: | 10 | Colour of the body: | white |
| Rated power of the luminaire [W]: | 11 | Dimensions [mm]: | ø300/90 |
| Supply voltage [V]: | 220 - 240 | Impact resistance: | IK10 |
| Frequency [Hz]: | 50 - 60 | Ingress protection: | IP44 |
| Luminous flux [lm]: | 1090 | Mounting version: | surface |
| Luminous efficacy [lm/W]: | 99 | Working temperature [°C]: | from -20 to +35 |
| Energy efficiency class: | A+ | Net weight of the luminaire [kg]: | 0.600 |
| Electrical protection class: | II | CE certificate: | 56/2015 |
| Colour temperature [K]: | 4000 | Index: | 206016/HV |
| Colur rendering index: | >80 | EAN: | 5905963206016/HV |
| Power factor: | 0.53 | Category type: | bulkheads |
| LED lifespan L70B50 [h]: | 50000 | Category of application: | residential |
| Beam angle [°]: | 120 | ETIM class: | EC002892 |
| Diffuser material: | PC | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Diffuser type: | OPAL | | |

*Tolerance+/- 10%

*The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.*

*Revision date: 2018-09-18*

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl

RoHS compliant — The luminaire complies with the EU ROHS Directive 2011/65/UE

This product is a subject to electric and electronic waste equipment regulations (WEEE).

CE 56/2015