TAO

LED's luminaire for 220-240V 50/60Hz supply tension
Luminaire pre-set for standard/LED lamps

Technical details
- Luminaire for pole top use on Ø60mm poles
- Silicone gaskets
- Polyester coating after a treatment specific for weathering resistance
- A2 stainless steel screws

Top cover
- Painted reinforced thermoplastic top cover

Diffuser
- Non yellowing opal PMMA (acrylic) diffuser

Housing
- Painted reinforced thermoplastic housing



Tao Led
Luminaire height 2mt
Road width 3mt
Pole spacing 7mt
Emed 10 lux
Emin 5 lux







Dimensions	Power	Metallic grey RAL 9006	Black	Green
311x255mm	11.3W 4000K 1920 lm	1015.182M	1015.182N	1015.182V
	11.3W 3000K 1856 lm	1015.184M	1015.184N	1015.184V
	*max 30W - E27	1015.101M	1015.101N	1015.101V

Max lamp dimension allowed
*(Ø60 L190mm)
Lamp not included

RECOMMENDED POLE

Slick and coloured Slick pole / **Rigo**

Total height			
1000mm	1400.200G	1400.200N	1409.200N
1500mm	1400.300G	1400.300N	1409.300N
2000mm	1400.400G	1400.400N	1409.400N

Mistral and coloured Mistral

Ø160mm	1480.000G	1480.000N

MADE IN ITALY