SFERA Ø400 LED - IP44

LED's luminaire for 220-240V 50/60Hz supply tension

Technical details
- For use on poles and brackets Ø60mm
- Silicone gaskets
- A2 stainless steel screws
- Electronic driver included
- Round LED circuit, 50 LEDs
- Power supplied at 500mA
- Uplight mounting

PMMA diffuser
- The polymethylmethacrylate (PMMA) spherical diffuser has exceptional transparency and resisitance to UV radiations
- It is available for uplight installation in transparent, white, or black semi-covered color and internally in reflective aluminium

Wiring
- Reinforced thermoplastic covering cone for wiring and driver recovery
- Reinforced thermoplastic anti-glare louver
- Reinforced thermoplastic top cover

IP44 base
- Reinforced black thermoplastic base
- Self regulating cable block

Uplight





Transparent



Semi-covered



Uplight wiring





I = Pole spacing (mt)
H = Height (mt)
Emed = Average illuminance (Lux)
Emin = Minimum illuminance (Lux)

	I mt	H mt	Emed Lux	Emin Lux
70W SAP	10	4	9	4
125W QE	10	4	9	6
15W LED	10	4	13	6

Luminaire with discharge lamp



Sfera Led 400





Conforms to all regional light laws against pollution

Dimensions	Power	White	Transparent	Semi covered
Ø400mm Uplight	15W 4000K 2200 lm	1080.582B	1080.582T	1010.582T
	15W 3000K 2100 lm	1080.584B	1080.584T	1010.584T

Data can be changed according to technological developments. For the latest updates we recommend you to visit our website marecoluce.it