SIEMENS

Data sheet 6GT2600-4AB00

Product type designation

MDS D460 transponder

Transponder MDS D460 for RF200/RF300 ISO/MOBY D PILL ISO 15693, Chip type FUJITSU MB89R118, 2000 byte FRAM User memory 16x 3 mm (DxH); Minimum order quantity 50 units



Suitability for operation	RF200, RF300, MOBY D

Radio frequencies	
Operating frequency / Rated value	13.56 MHz
Range / maximum	160 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
Protocol / with radio transmission	ISO 15693
Transfer rate / with radio transmission / maximum	26.5 kbit/s
Product feature / multitag-capable	Yes

Electrical data	
Product component / Backup battery	No

Memory	
Type of memory	FRAM
Storage capacity / of the user memory	2000 byte
Type of memory organization	UID (fixed code) 8 bytes, user memory 2000 bytes, configuration memory 40 bytes
Number of read cycles / at ambient temperature < 40 °C / maximum	1000000000000

Subject to change without notice
© Copyright Siemens

Number of write cycles / at ambient temperature < 40 °C / maximum	1000000000000
Data retention time / at ambient temperature < 40 °C / not less than	10 y
Property of memory	Block-by-block write protection of the user memory
Type of transponder chip used	Fujitsu MB89R118

Mechanical data

Material	PPS
Color	black
Mounting distance / relating to metal surfaces / recommended / minimum	10 mm

Ambient conditions

Ambient temperature	
• during read/write access	-25 ... +85 °C
• outside the read/write area	-40 ... +100 °C
• during storage	-40 ... +100 °C
Protection class IP	IP67 / IPx9K
Shock resistance	According to DIN EN 60721-3-7 Class 7 M3
Shock acceleration	500 m/s²
Vibrational acceleration	200 m/s²

Design, dimensions and weights

Height	3 mm
Diameter	16 mm
Net weight	3 g
Mounting type	patching, gluing

Product features, product functions, product components / general

Product feature	
• printable	No

Standards, specifications, approvals

Certificate of suitability	
• IECEx	No
MTBF	228 y

accessories

accessories	Mounting support and spacer

Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens

• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	04/01/2020

© Copyright Siemens