Karta katalogowa produktu
PP PAR16 3.7 W/930 GU10

PARATHOM PRO PAR16 | Reflektorowe lampy LED PAR16 z możliwością regulacji strumienia



- Shops and exhibition rooms Domestic applications Commercial applications Accent lighting Outdoor use in outdoor luminaires only (minimum IP65)

- Quick, simple and safe replacement without rewiring Design, dimensions, luminous flux comparable to an incandescent or halogen lamp Low maintenance costs thanks to long lifetime No UV and near-IR radiation in the light beam Stepless dimming Very high dimmer compatibility, see also "www.ledvance.com/dim" Instant 100 % light, no warm-up time



OSRAM GmbH. Wszystkie prawa zastrzeżone.

Dane techniczne

Dane elektryczne

ZLDV_Rated wattage [AGGR]	3.70 W
ZLDV_Nominal wattage [AGGR]	3.70 W
ZLDV_Nominal voltage [AGGR]	220…240 V
ZLDV_Claimed equiv. conventional lamp power [AGGR]	35 W
ZLDV_Operating frequency [AGGR]	50…60 Hz

Dane fotometryczne

ZLDV_Nominal luminous flux [AGGR]	230 lm
ZLDV_Rated luminous flux [AGGR]	230 lm
ZLDV_Rated color temperature [AGGR]	3000 K
ZLDV_Color rendering index Ra [AGGR]	97
ZLDV_Light color (designation) [AGGR]	Warm White
ZLDV_Standard deviation of color matching [AGGR]	≤3 sdcm
ZLDV_Nominal useful luminous flux 90° [AGGR]	230 lm
ZLDV_Rated useful luminous flux 90° [AGGR]	230 lm
ZLDV_Rated peak intensity [AGGR]	690 cd
ZLDV_Lumen main.fact.at end of nom.life time [AGGR]	0.70

Dane świetlne

ZLDV_Beam angle [AGGR]	36 °
ZLDV_Nominal beam angle [AGGR]	36 °
ZLDV_Rated beam angle (half peak value) [AGGR]	36.00 °
ZLDV_Starting time [AGGR]	< 0.5 s

Wymiary i waga



ZLDV_Overall length [AGGR]	55.0 mm

OSRAM GmbH. Wszystkie prawa zastrzeżone.

ZLDV_Diameter [AGGR]	51.0 mm
ZLDV_Outer bulb [AGGR]	PAR51
ZLDV_Length [AGGR]	55.0 mm
ZLDV_Maximum diameter [AGGR]	51.0 mm

Trwałość

ZLDV_Nominal lamp life time [AGGR]	40000 h
ZLDV_Rated lamp life time LEDr [AGGR]	40000 h
ZLDV_Number of switching cycles [AGGR]	1000000

Dodatkowe dane produktu

ZLDV_Base (standard designation) [AGGR]	GU10
ZLDV_Mercury content [AGGR]	0.0 mg
ZLDV_Mercury-free [AGGR]	Yes
Zgodnie z Dyrektywą WEEE	Tak
ZLDV_Product remark [AGGR]	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Możliwości

ZLDV_Dimmable [AGGR]	Yes

Certyfikaty i Normy

ZLDV_Energy efficiency class [AGGR]	A
ZLDV_Energy consumption [AGGR]	4 kWh/1000h

Kraj - specyficzna kategoryzacja

ZLDV_Order reference [AGGR]	LPPAR16D3536 3,

Dane logistyczne

Kod produktu	Opis produktu	Opakowanie (liczba produktów / opakowanie)	Wymiary (długość x szerokość x wysokość)	Objętość	Waga brutto
4058075259997	PP PAR16 3.7 W/930 GU10	Karton wysyłkowy 10 Pieces Składane pudełko	257 mm x 110 mm x 70 mm	1.98 dm^3	595.00 g

OSRAM GmbH. Wszystkie prawa zastrzeżone.

Wymieniony kod produktu oznacza najmniejszą ilość produktu, jaka może być zamówiona. Jednostka transportowa może zawierać jedną sztukę lub więcej. Składając zamówienie prosimy o zamawianie ilości odpowiadających jednej lub wielokrotności jednostki transportowej.

Odnośniki/łącza

Kompatybilność funkcji ściemniania, patrz
- www.osram.com/DIM

Więcej produktów i aktualne informacje na temat lamp LED na stronie
- www.osram.pl/ledlamps

Gwarancja, patrz
- www.osram.pl/gwarancja

Oświadczenie

Zastrzega się możliwość zmian bez uprzedzenia. Błędy i ominięcia są możliwe. Należy zawsze upewnić się czy korzystasz z najnowszej wersji katalogu.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany

OSRAM GmbH. Wszystkie prawa zastrzeżone.