PRODUCT CARD

2019-01-18

SO274S

Uchwyt odciągowy



Typ	SO274S
GTIN	6418677446696
Nazwa	Uchwyt odciągowy 4x(25-50) mm², nakrętki śrub z łbami zrywalnymi
Opis	Uchwyt odciągowy do trwałego zamocowania przewodu wiązkowego. Śruby dociskowe uchwytu posiadaja nakrętki z łbem zrywalnym.

Specyfikacje techniczne

Wymiary

Masa:	1 kg
Przekrój żyły:	4x25-50
Średnica żyły:	7.0 ... 10.2 mm

Mechanical

SMFL:	4x25 mm² 13 kN / 4x35 mm² 17.8 kN / 4x50 mm² 25 kN
Moment dokręcenia:	47 Nm

Ratings

ETIM 7:	EC003516 Accessories for cross arm for utility pole

Specyfikacja

Use:	For the termination of 4 core overhead cables. SMFL
Construction:	

Construction:

Construction	Material
Steel parts	Hot-dip galvanised steel
Shear-head nuts	Aluminium alloy
Composite parts	Fibreglass reinforced, frost, heat and UV-radiation resistant composite material.
Washer	Stainless steel

Installation: The clamp is opened and the wires are inserted between the wedges. Springs keepthe clamp in an open position during an installation. Nuts must be tightened up uniformly until shear-head brakes. After reaching a proper torque retightening is not allowed.

Tools required: Ratchet wrench CT164

Markings: ENSTO, SO274S, 4x 25-50 mm², 47 Nm

Standard: EN50483-2

ETIM

ETIM

Type of accessory: Other

Opakowanie

Opakowanie

Unit: PCS

Size: 10

Length: 385 mm

Width: 260 mm

Height: 165 mm

Weight (net): 10 kg

Weight (brt): 10.267 kg

Volume: 0.0165

Pallet package

Unit: PCS

Size: 540

Length: 1200 mm

Width: 800 mm

Height: 1140 mm

Weight (net): 540 kg

Weight (brt): 560 kg

Volume: 1.0944

Straszyn

ul. Starogardzka 17a
83-010 Straszyn
Polska

Email biuro@ensto.com
Tel. 58 692 40 00

www.ensto.com