



Material cable sheath	PE
Cable sheath diameter (approx.)	6,2 mm
max. bandwidth	250 MHz
Cable type	round cable
Inner conductor material	CCA (copper-clad aluminium)
AWG	24/1 (solid)
Shielding class	U/UTP
Connection, type	RJ45 male (8P8C)
Latch protection	both sides
Contacting	EIA/TIA-568B

Goobay

CAT 6 Outdoor-patch cable, U/UTP, black

CCA material

- unshielded LAN/network cable to connect network components with 2 RJ45 connectors
- UV- and water resistant
- double outer jacket
- with gold plated PINs
- with strain relief and latch protection
- suitable for 10/100/1000 Mbit-networks
- pair-sequence acc. to EIA/TIA 568B



Cable length	Bulk
10.00 m	94389
15.00 m	94391
20.00 m	94392
30.00 m	94393
40.00 m	94394
50.00 m	94395
60.00 m	94396
75.00 m	94397



Material Kabelmantel	PVC
Durchmesser Kabelmantel (ca.)	6 mm
max. Bandbreite	250 MHz
Kabeltyp	Rundkabel
Innenleiter, Material	CU (Kupfer)
AWG	26/7 (stranded)
Schirmungsklasse	F/UTP
Anzahl Schirmungen	1 x
Typ 1, Schirmung	Folie (Alu)
Anschluss, Typ	RJ45-Stecker (8P8C)
Anschluss 2, Typ	RJ45-Buchse (8P8C)
Anschluss, Schirmung	ja
Rastnasenschutz	unilaterally

Goobay

CAT 6 extension cable, F/UTP

with mounting flange

- mounting, for example, to a slot bracket, cable duct or an enclosure with corresponding opening
- with mounting flange, hole spacing (thread): 25 mm
- shielded network cable extension for extending your network components
- outer shield: foil screening
- with 3µ gold plated PINs
- plug with latch protection, molded RJ45 socket
- pin out: 1:1, pair-sequence acc. to EIA/TIA 568B







Cable length	black	white
	Bulk	Bulk
0.50 m	77554	77555
1.00 m	77556	77557
1.50 m	77558	77559
2.00 m	77560	77561
3.00 m	77562	77563
4.00 m	77564	77565
5.00 m	77566	77567
7.50 m	77568	77569
10.00 m	77570	77571