Control cable | PVC | chainflex® CF6

10 million
Guaranteed double strokes

6.8 x d
Bend radius e-chain®

100 m
Travel distance, e-chain®

- For heavy duty applications
- PVC outer jacket
- Shielded
- Oil-resistant
- Flame retardant



Example image

Dynamic information

Bend radius	**e-chain® linear**	min. 6.8 x d
	flexible	min. 5 x d
	fixed	min. 4 x d
Temperature	**e-chain® linear**	+5 °C up to +70 °C
	flexible	-5 °C up to +70 °C (following DIN EN 60811-504)
	fixed	-15 °C up to +70 °C (following DIN EN 50305)
v max.	**unsupported**	10 m/s
	gliding	5 m/s
a max.		80 m/s²
Travel distance		Unsupported travels and up to 100 m for gliding applications, Class 5

Cable structure

Conductor	Finely stranded conductor consisting of bare copper wires (following DIN EN 60228).
Core insulation	**Cores ≤ 0.5 mm²:** Mechanically high-quality TPE mixture. **Cores ≥ 0.75 mm²:** Mechanically high-quality PVC mixture.
Core structure	**Number of cores < 12:** Cores wound in a layer with short pitch length. **Number of cores ≥ 12:** Cores wound in bundles which are then wound around a high tensile strength centre element, all with optimised short pitch lengths and directions. Especially low-torsion structure.
Core identification	**Cores < 0.5 mm²:** Colour code in accordance with DIN 47100. **Cores ≥ 0.5 mm²:** Black cores with white numbers, one green-yellow core.
Inner jacket	PVC mixture adapted to suit the requirements in e-chains®.
Overall shield	Extremely bending-resistant braiding made of tinned copper wires. Coverage linear approx. 70 %, optical approx. 90 %
Outer jacket	Low-adhesion, oil-resistant PVC mixture, adapted to suit the requirements in e-chains® (following DIN EN 50363-4-1). Colour: Moss green (similar to RAL 6005)
CFRIP®	Strip cables faster: a tear strip is moulded into the inner jacket Video ▶ www.igus.eu/CFRIP

Electrical information

Nominal voltage	300/500 V (following DIN VDE 0298-3)
Testing voltage	2000 V (following DIN EN 50395)

EU04.2019

Class 5.5.2.1

Basic requirements	low	1	2	3	4	**5**	6	7	highest
Travel distance	unsupported	1	2	3	4	**5**	6		≥ 400 m
Oil resistance	none	1	**2**	3	4				highest
Torsion	none	**1**	2	3	4				±360°

Properties and approvals

UV resistance	Medium
Oil resistance	Oil-resistant (following DIN EN 50363-4-1), Class 2
Flame retardant	According to IEC 60332-1-2, CEI 20-35, FT1, VW-1
Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
UL/CSA	**Cores < 0.75 mm²:** Style 10492 and 2570, 600 V, 80 °C **Cores ≥ 0.75 mm²:** Style 11113 and 2570, 600 V, 80 °C
NFPA	Following NFPA 79-2018, chapter 12.9
EAC	Certificate No. RU C-DE.ME77.B.01254 (TR ZU)
CTP	Certificate No. C-DE.PB49.B.00416 (Fire protection)
CEI	Following CEI 20-35
Lead-free	Following 2011/65/EC (RoHS-II)
Cleanroom	According to ISO Class 2. The outer jacket material of this series complies with CF5.10.07 - tested by IPA according to standard DIN EN ISO 14644-1
CE	Following 2014/35/EU

Guaranteed service life (details see page 22-23)

Double strokes*	5 million		7.5 million		10 million	
Temperature, from/to [°C]	< 10 m	≥ 10 m	< 10 m	≥ 10 m	< 10 m	≥ 10 m
	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
+5/+15	7.5	10	8.5	11	9.5	12
+15/+60	6.8	7.5	7.8	8.5	8.8	9.5
+60/+70	7.5	10	8.5	11	9.5	12

* Higher number of double strokes? Service life calculation online ▶ www.igus.eu/chainflexlife

Typical mechanical application areas

- For heavy duty applications, Class 5
- Unsupported travels and up to 100 m for gliding applications, Class 5
- Light oil influence, Class 2
- No torsion, Class 1
- Preferably indoor applications, but also outdoor ones at temperatures > 5 °C
- Storage and retrieval units for high-bay warehouses, machining units/ packaging machines, quick handling, indoor cranes

Control cable | PVC | chainflex® CF6

Strip cables 50 % faster

Class 5.5.2.1

Basic requirements	low	1	2	3	4	**5**	6	7	highest
Travel distance	unsupported	1	2	3	4	**5**	6		≥ 400 m
Oil resistance	none	1	**2**	3	4	highest			
Torsion	none	**1**	2	3	4	±360°			

CF6
PVC
6.8 x d



Example image

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CF6.02.04	(4x0.25)C	7.0	29	61
CF6.02.25	(25x0.25)C	14.5	111	260
CF6.03.05	(5x0.34)C	7.5	37	90
CF6.05.02	(2x0.5)C	7.0	29	77
CF6.05.05	(5G0.5)C	8.5	49	106
CF6.05.07	(7G0.5)C	10.0	64	127
CF6.05.09	(9G0.5)C	12.0	70	153
CF6.05.12	(12G0.5)C	13.0	98	232
CF6.05.18	(18G0.5)C	15.0	145	286
CF6.05.25	(25G0.5)C	17.5	192	399
CF6.07.03	(3G0.75)C	8.0	46	98
CF6.07.04	(4G0.75)C	8.5	56	113
CF6.07.05	(5G0.75)C	9.0	67	128
CF6.07.07	(7G0.75)C	10.5	86	152
CF6.07.12	(12G0.75)C	14.0	128	266
CF6.07.18	(18G0.75)C	17.5	196	400
CF6.07.25	(25G0.75)C	19.5	265	536
CF6.10.03	(3G1.0)C	8.0	54	107
CF6.10.04	(4G1.0)C	9.0	64	116
CF6.10.05	(5G1.0)C	9.5	77	136
CF6.10.07	(7G1.0)C	12.0	103	205
CF6.10.12	(12G1.0)C	15.0	161	319
CF6.10.18	(18G1.0)C	19.0	245	482
CF6.10.25	(25G1.0)C	21.0	322	595
CF6.15.03	(3G1.5)C	9.0	72	122
CF6.15.04	(4G1.5)C	9.5	87	155
CF6.15.05	(5G1.5)C	10.5	105	177
CF6.15.07 [17)]	(7G1.5)C	13.0	146	258
CF6.15.12	(12G1.5)C	17.0	225	375
CF6.15.18	(18G1.5)C	21.0	345	581
CF6.15.25	(25G1.5)C	24.0	462	865
CF6.15.36	(36G1.5)C	30.0	675	1293
CF6.25.04	(4G2.5)C	11.5	131	222

[17)] When using the cables with “7 G 1.5 mm²” and “7 G 2.5 mm²” minimum bend radius must be 17.5 x d with gliding travel distance ≥ 5 m.

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core **x =** without earth core

Order example: CF6.02.04 – to your desired length (0.5 m steps)
CF6 chainflex® series .02 Code nominal cross section .04 Number of cores

Online order ▶ www.chainflex.eu/CF6

Delivery time 24hrs or today.
Delivery time means time until goods are shipped.



chainflex® CF5 and CF6 control cables (green) as well as CF211 measuring system cables (grey) in a screwing station of a car factory. e-chain®: System E4/00 with chainfix clip strain relief devices.