Motor cable | PVC | chainflex® CF885



Example image

5 million Guaranteed double strokes

15 x d Bend radius e-chain®

10 m Travel distance, e-chain®

- For flexing applications
- PVC outer jacket
- Flame retardant

Dynamic information

Bend radius	**e-chain® linear**	min. 15 x d
	flexible	min. 12 x d
	fixed	min. 8 x d
Temperature	**e-chain® linear**	+5 °C up to +70 °C
	flexible	-5 °C up to +70 °C (following DIN EN 60811-504)
	fixed	-15 °C up to +70 °C (following DIN EN 50305)
v max.	**unsupported**	3 m/s
a max.		20 m/s²
Travel distance		Unsupported travels up to 10 m, Class 1

Cable structure

Conductor	Conductor consisting of bare copper wires (according to DIN EN 60228).
Core insulation	Mechanically high-quality, especially low-capacitance TPE mixture.
Core structure	Cores wound with an optimised pitch length.
Core identification	Black cores with white numbers, one green-yellow core. 1. Core: U / L1 / C / L+ 2. Core: V / L2 3. Core: W / L3 / D / L-
Outer jacket	Low-adhesion PVC mixture, adapted to suit the requirements in e-chains®. Colour: Pastel orange (similar to RAL 2003)

Electrical information

Nominal voltage	600/1000 V (following DIN VDE 0298-3)
Testing voltage	4000 V (following DIN EN 50395)

Class 3.1.1.1

Basic requirements	low	1	2	**3**	4	5	6	7	highest
Travel distance	unsupported	**1**	2	3	4	5	6		≥ 400 m
Oil resistance	none	**1**	2	3	4				highest
Torsion	none	**1**	2	3	4				±360°

Properties and approvals

Flame retardant	According to IEC 60332-1-2, CEI 20-35, FT1, VW-1
Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
UL/CSA	Style 10492 and 2570, 1000 V, 80 °C
NFPA	Following NFPA 79-2018, chapter 12.9
EAC	Certificate No. RU C-DE.ME77.B.01561 (TR ZU)
CTP	Certificate No. C-DE.PB49.B.00450 (Fire protection)
Lead-free	Following 2011/65/EC (RoHS-II)
CE	Following 2014/35/EU

Guaranteed service life (details see page 22-23)

Double strokes*	1 million	3 million	5 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
+5/+15	17.5	18.5	19.5
+15/+60	15	16	17
+60/+70	17.5	18.5	19.5

* Higher number of double strokes? Service life calculation online ▶ www.igus.eu/chainflexlife

Typical mechanical application areas

- For flexing applications, Class 3
- Especially for unsupported travels, Class 1
- Without influence of oil, Class 1
- No torsion, Class 1
- Preferably indoor applications
- Wood/stone processing, Packaging industry, supply systems, Handling, adjusting equipment

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CF885.15.04	4G1.5	9.0	60	118
CF885.25.04	4G2.5	10.5	100	176
CF885.40.04	4G4.0	12.0	159	256
CF885.60.04	4G6.0	14.0	238	358
CF885.100.04	4G10	16.5	396	546
CF885.160.04	4G16	20.0	627	843

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core **x =** without earth core

CF885
PVC
15 x d