GLC0315T4C1

4 polowy rozłącznik w układzie przełącznym wg IEC/EN, 315A



Product designation			Changeover Switch
Product type designation			GLC
Number of poles		nr.	4
Operating voltage type			AC
Contact characteristics			
IEC Conventional free air thermal current Ith		A	315
Rated insulation voltage Ui IEC/EN		V	1000
Rated impulse withstand voltage Uimp		kV	12
Operating current Ie			
AC31B			
	400V	A	315
	500V	A	315
	690V	A	315
AC32B			
	400V	A	315
	500V	A	315
	690V	A	315
AC33B			
	400V	A	250
	500V	A	250
	690V	A	250
Power dissipation per pole max		W	6.5
Rated operational power AC23A			
	400V	kW	140
	690V	kW	250
Reactive power for control of capacitors at			
Rated short time current (1s) Icw (rms)		kA	8
Conditional short-circuit current (rms)		kA	100
Short-circuit protection with fuse		Class/A	gG/315
Making capacity AC23A 400V		A	2500
Breaking capacity AC23A 400V		A	2000
Mechanical life		cycles	20000
Mechanical features			
Operating position			
	normal		Vertical plan
	allowable		Any
Fixing			Screw
Terminals			
	type		M8 x 20
Tightening torque for terminals			
	min	Nm	15
	max	Nm	22
	min	lbin	132
	max	lbin	194

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

GLC0315T4C1


4 polowy rozłącznik w układzie przełącznym wg IEC/EN, 315A

Conductor section			
	IEC min	mm²	1X182
	IEC max	mm²	2X185
	AWG/kcmil min		1X400
	AWG/kcmil max		2X350


Ambient conditions

Operating temperature			
	min	°C	-25
	max	°C	+55
Storage temperature			
	min	°C	-40
	max	°C	+70
Max altitude		m	3000

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

IEC/EN 60947-1

IEC/EN 60947-3

ETIM 6 classification

EC000066 - Power contactor, AC switching

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding