# PRODUCT FEATURES PZB, PZB1

>>Conductor coated with Polwinit OMY lub H05VV-F
>>Robust drum construction resistant to impact
>>Different drum sizes
>>Insulated grip for to item be easy carried
>>Blocking against inadvertent unrolling
>>Thermal fuse
>>Orange conductor, as an option black
>>Manufactured according to Polish standard PN-IEC 61242, for use inside and outside



3x1,5 mm² | 1100W 250V~ | 3600W 250V~ | Produkt Polski

## PRZEDŁUŻACZE ZWIJANE NA BĘBNIE Z ZABEZPIECZENIEM TERMICZNYM, 4-KROTNE Z UZIEMIENIEM, METALOWY STOJAK

EXTENSION REELS WITH THERMAL PROTECTION

| długość/m length/m | symbol cat. No | szt./op. pcs./pcg. | kod EAN EAN Code | waga weight |
|---|---|---|---|---|
| 20 | PZB-40-20Y | 1 | 5902694040209 | 3,15 |
| 25 | PZB-40-25Y | 1 | 5902694040254 | 3,48 |
| 30 | PZB-40-30Y | 1 | 5902694040308 | 3,89 |
| 35 | PZB-40-35Y | 1 | 5902694040353 | 4,30 |
| 40 | PZB-40-40Y | 1 | 5902694040407 | 4,71 |
| 50 | PZB-40-50Y | 1 | 5902694040506 | 5,45 |



3x1 mm² | 700W 250V~ | 2300W 250V~ | Produkt Polski

## PRZEDŁUŻACZE ZWIJANE NA BĘBNIE Z ZABEZPIECZENIEM TERMICZNYM, 3-KROTNE Z GNIAZDAMI BRYZGOSZCZELNYMI (IP44) Z UZIEMIENIEM, METALOWY STOJAK

EXTENSION REELS WITH SPLASH-PROOF SOCKETS (IP44) AND THERMAL PROTECTION

| długość/m length/m | symbol cat. No | szt./op. pcs./pcg. | kod EAN EAN Code | waga weight |
|---|---|---|---|---|
| 20 | PZB-111-20Y/1 | 1 | 5902694727209 | 1,90 |
| 25 | PZB-111-25Y/1 | 1 | 5902694737253 | 2,20 |
| 40 | PZB-111-40Y/1 | 1 | 5902694737857 | 3,60 |



3x1 mm² | 700W 250V~ | 2300W 250V~ | Produkt Polski | 10A 250V~

## PRZEDŁUŻACZE ZWIJANE NA BĘBNIE Z ZABEZPIECZENIEM TERMICZNYM, 3-KROTNE Z UZIEMIENIEM

EXTENSION REELS WITH 3-WAY, THERMAL PROTECTION, GRUNDED

| długość/m length/m | symbol cat. No | szt./op. pcs./pcg. | kod EAN EAN Code | waga weight |
|---|---|---|---|---|
| 6 | PSZ-306 | 1 | 5902694703067 | 0,80 |
| 9 | PSZ-309 | 1 | 5902694703098 | 0,95 |
| 12 | PSZ-3012 | 1 | 5902694730124 | 1,15 |



3x1,5 mm² | 1100W 250V~ | 3600W 250V~ | Produkt Polski

## PRZEDŁUŻACZE ZWIJANE NA BĘBNIE Z ZABEZPIECZENIEM TERMICZNYM, 3-KROTNE Z GNIAZDAMI BRYZGOSZCZELNYMI (IP44) Z UZIEMIENIEM, METALOWY STOJAK

EXTENSION REELS WITH SPLASH-PROOF SOCKETS (IP44) AND THERMAL PROTECTION

| długość/m length/m | symbol cat. No | szt./op. pcs./pcg. | kod EAN EAN Code | waga weight |
|---|---|---|---|---|
| 20 | PZB-111-20Y | 1 | 5902694111213 | 3,20 |
| 25 | PZB-111-25Y | 1 | 5902694727254 | 3,70 |
| 30 | PZB-111-30Y | 1 | 5902694727308 | 4,00 |
| 35 | PZB-111-35Y | 1 | 5902694111350 | 4,30 |
| 40 | PZB-111-40Y | 1 | 5902694727407 | 4,80 |
| 50 | PZB-111-50Y | 1 | 5902694727506 | 5,50 |