Connection cables without connector



Symbol	Supply voltage	Conductor's structure	Length	Outer wire diameter	Insulation resistance	Reference standard
SP1,00 (2x0,50)	250 V	2x0,5 mm²	1,0 m	3,13 x 5,0 mm	0,012 MΩ/km	IEC60884-1:2006
SP1,00 (2x0,75)	250 V	2x0,75 mm²	1,0 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006
SP1,50 (2x0,50)	250 V	2x0,5 mm²	1,5 m	3,13 x 5,0 mm	0,012 MΩ/km	IEC60884-1:2006
SP1,50 (2x0,75)	250 V	2x0,75 mm²	1,5 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006
SP1,60 (2x0,50)	250 V	2x0,5 mm²	1,6 m	3,13 x 5,0 mm	0,012 MΩ/km	IEC60884-1:2006
SP1,60 (2x0,75)	250 V	2x0,75 mm²	1,6 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006
SP1,90 (2x0,50)	250 V	2x0,5 mm²	1,9 m	3,13 x 5,0 mm	0,012 MΩ/km	IEC60884-1:2006
SP1,90 (2x0,75)	250 V	2x0,75 mm²	1,9 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006
SP2,00 (2x0,50)	250 V	2x0,5 mm²	2,0 m	3,13 x 5,0 mm	0,012 MΩ/km	IEC60884-1:2006
SP2,00 (2x0,75)	250 V	2x0,75 mm²	2,0 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006
SP2,30 (2x0,75)	250 V	2x0,75 mm²	2,3 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006
SP2,50 (2x0,75)	250 V	2x0,75 mm²	2,5 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006
SP3,00 (2x0,75)	250 V	2x0,75 mm²	3,0 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006
SP3,50 (2x0,75)	250 V	2x0,75 mm²	3,5 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006
SP4,00 (2x0,75)	250 V	2x0,75 mm²	4,0 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006
SP4,50 (2x0,75)	250 V	2x0,75 mm²	4,5 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006
SP5,00 (2x0,75)	250 V	2x0,75 mm²	5,0 m	3,2 x 5,2 mm	0,01 MΩ/km	IEC60884-1:2006

Available insulation colour: white, brown, black, silver, gold, transparent.

RoHS REACH CE

Description

Connection cable terminated with 230 V plug at one end. Cable structure: two-wire, copper, multi-stranded. Cable cross-section: flat. Uninsulated tinned conductors at the other end.

Application

Designed for the connection of portable electric receivers to 230 V AC. Conformity with RoHS, REACH.