Karta katalogowa | Numer produktu: 770-121

Zaczep ryglujący; Do połączeń swobodnych; do obsługi ręcznej; biały

www.wago.com/770-121



Kolor:

Opis artykułu

Locking device *WINSTA*® MIDI

When using the locking device from the *WINSTA*® MIDI product line, zero-defect installation is ensured. With WAGO, you can enjoy the advantages of a large selection of accessories for the WINSTA® product line.

Our *WINSTA*® MIDI product line guarantees total flexibility for the installation of applications. Through its Push-in CAGE CLAMP® spring pressure connection technology, it achieves time-saving, error-free installation and offers customization for meeting all installation requirements.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

WINSTA® is the pluggable connection system that is perfectly tailored to the strict requirements of electrical installation. It offers error-free installation of cables and components, quickly and reliably. Now you can also cut installation costs without compromising quality and safety: The

Dokonywanie zmian zastrzeżone. Należy stosować się do dokumentacji technicznej produktów.

WAGO ELWAG sp. z o. o.
ul. Piękna 58 a
50-506 Wrocław
Tel.: +48 71 3602972 | Fax: +48 71 3602999
Email: wago.elwag@wago.com

Masz pytania dotyczące naszych produktów?
Jesteśmy do Twojej dyspozycji pod numerem telefonu +48 71 360 29 70.

WINSTA® MIDI accessory reduces the need for servicing and prevents unnecessary downtime.

- for automation controllers
- quick replacement of defective units during ongoing operation

Data
Parametry zacisków

Connection 1

Sposób otwierania zacisku	Przycisk ręczny

Dane mechaniczne

Odpowiedni	do połączeń swobodnych; montaż ręczny

Dane materiałowe

Note on material data	Information on material data can be found here
Kolor	biały
Materiał izolacyjny	Poliamid (PA66)
Klasa palności wg UL 94	V0
Obciążenie ogniowe	0,017 MJ
Masa	0,6 g

Warunki środowiskowe

Temperatura montażu	-5 … +40 °C
Temperatura dopuszczalna długotrwale	-35 … +85 °C
Wskazówka dot. temperatury dopuszczalnej długotrwale	elementy izolacyjne do temperatury ≤ 105°C

Dokonywanie zmian zastrzeżone. Należy stosować się do dokumentacji technicznej produktów.

WAGO ELWAG sp. z o. o.
ul. Piękna 58 a
50-506 Wrocław
Tel.: +48 71 3602972 | Fax: +48 71 3602999
Email: wago.elwag@wago.com

Masz pytania dotyczące naszych produktów?
Jesteśmy do Twojej dyspozycji pod numerem telefonu +48 71 360 29 70.