

Pluggable Modules - Diode Gates


	Diode gate module with 3, 5, 7 or 9 diodes 1 N 4007, common anode Module width see Item No.	Diode gate module with 3, 5, 7 or 9 diodes 1 N 4007, common cathode Module width see Item No.











WSB marker card
- Marking V; Item No.: 209-784
- Marking 1 ... 10; Item No.: 209-702
- Marking +/-; Item No.: 209-652

5 cards, each containing 10 strips with 10 markers

Description	Module width	Item No.	Pack. Unit	Module width	Item No.	Pack. Unit
Diode gate module with 3 diodes	10 mm / 0.394 in	**286-803**	1	10 mm / 0.394 in	**286-813**	1
with 5 diodes	15 mm / 0.591 in	**286-805**	1	15 mm / 0.591 in	**286-815**	1
with 7 diodes	20 mm / 0.787 in	**286-807**	1	20 mm / 0.787 in	**286-817**	1
with 9 diodes	25 mm / 0.984 in	**286-809**	1	25 mm / 0.984 in	**286-819**	1

Technical Data

Accessories see pages 138 ... 139

Accessories see pages 138 ... 139

Operating voltage	250 V AC/DC	250 V AC/DC
Peak reverse voltage	1000 V	1000 V
Rectified current for each diode, resistive	1 A	1 A
Nominal voltage acc. to VDE 0110 Part 1/4.97, IEC 60664-1	250 V / 4 kV / 3	250 V / 4 kV / 3
Ambient operating temperature	-25 °C ... +40 °C	-25 °C ... +40 °C

Accessories

		Item No.	Pack. Unit		Item No.	Pack. Unit
Terminal block for pluggable modules,						
with 2-conductor terminal blocks, orange separator ❶	12 mm / 0.472 in wide	**280-618**	1	12 mm / 0.472 in wide	**280-618**	1
with 4-conductor terminal blocks, orange separator ❷	12 mm / 0.472 in wide	**280-608**	1	12 mm / 0.472 in wide	**280-608**	1
with 4-conductor terminal blocks, marker plate ❷	15 mm / 0.591 in wide	**280-762**	1	15 mm / 0.591 in wide	**280-762**	1
Terminal block for pluggable modules,						
with 2-conductor terminal blocks, orange separator ❶	17 mm / 0.669 in wide	**280-619**	1	17 mm / 0.669 in wide	**280-619**	1
with 4-conductor terminal blocks, orange separator ❷	17 mm / 0.669 in wide	**280-609**	1	17 mm / 0.669 in wide	**280-609**	1
with 4-conductor terminal blocks, marker plate ❷	20 mm / 0.787 in wide	**280-763**	1	20 mm/ 0.787 in wide	**280-763**	1
Terminal block for pluggable modules,						
with 2-conductor terminal blocks, orange separator ❶	22 mm / 0.866 in wide	**280-638**	1	22 mm / 0.866 in wide	**280-638**	1
with 4-conductor terminal blocks, orange separator ❷	22 mm / 0.866 in wide	**280-628**	1	22 mm / 0.866 in wide	**280-628**	1
with 4-conductor terminal blocks, marker plate ❷	25 mm / 0.984 in wide	**280-764**	1	25 mm / 0.984 in wide	**280-764**	1
Terminal block for pluggable modules,						
with 2-conductor terminal blocks, orange separator ❶	27 mm / 1.063 in wide	**280-639**	1	27 mm / 1.063 in wide	**280-639**	1
with 4-conductor terminal blocks, orange separator ❷	27 mm / 1.063 in wide	**280-629**	1	27 mm / 1.063 in wide	**280-629**	1
with 4-conductor terminal blocks, marker plate ❷	30 mm / 1.181 in wide	**280-765**	1	30 mm / 1.181 in wide	**280-765**	1
wire range 0.08 mm² ... 2.5 mm² / AWG 28 ... 14;						
stripped length 8 ... 9 mm / 0.33 in						