TM TECHNOLOGIE



TM.ONTEC S20 M1U 60 NM ST

TM-S2.MUSTN160W





PARAMETERS

Application	anti-panic lighting
IP	IP65/IK08
IK	IK08
Version	ST – for button test
Power supply	210÷250 V AC 50÷60 Hz
Power supply CB	186÷254 V DC
Temperature range	5-40 °C
Material	PC
Colour	RAL9003
Duration time	1 h
Operating mode	NM
Active power	1.95 W
Insulation class	2
Luminous flux	125 lm
Battery	LiFePO4/C 3.2V 1.5Ah
Dimming mode	no

PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	3,5 - 1h | 3,0 - 3h	7,0 - 1h | 8,0 - 3h
3,0	3,5 - 1h | 3,5 - 3h	9,5 - 1h | 8,0- 3h
4,0	4,5 - 1 h | 4,0 - 3h	11,5 - 1 h | 9,5 - 3h
5,0	5,0 - 1h | 4,0 - 3 h	13,0 - 1 h | 11,0 - 3 h
6,0	5,0 - 1 h | 3,5 - 3h	15,0 - 1 h | 12,5 - 3h
7,0	5,0 - 1h | 3,5 - 3h	16,5 - 1 h | 13,5 - 3h
8,0	5,5 - 1 h | 3,5 - 3h	18,0 - 1 h | 14,0 - 3h
9,0	5,5 - 1h | 3,0 - 3h	19,0 - 1h | 14,5 - 3h
10,0	5,5 - 1 h | 2,0 - 3h	20,0 - 1h | 15,0 - 3h