Product data sheet
Characteristics

NSYLAMT5LD2
Cost-effective LED Lamps - 120/230 V AC - 10W



Main

Range of product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or component type	Lamp
Device application	Multi-purpose
Device composition	1 x lamp 2 x cable 1 x fixing elements
Power factor	0.9

Complementary

Outlet standard	Without socket
Rated lamp wattage	10 W
[Ue] rated operational voltage	120/230 V AC - 50/60 Hz
Bulb base	Integral LED
Bulb type	LED
Control type	Built-it switch
Luminous flux	1100 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 3 m supplied Cable quick connector 1 m supplied
Mounting support	Cross rails Metal parts
Fixing mode	Screws Magnetic fixing
Range compatibility	Spacial Thalassa
Length	560 mm
Height	30.5 mm
Colour	Aluminium

NSYLAMT5LD2

Environment

IP degree of protection	IP20 conforming to IEC 60529

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Electrical insulation class	Class I
Standards	IEC 60598
Ambient air temperature for operation	-16...65 °C
Ambient air temperature for storage	-10...60 °C

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold