Product Information

tesa® extra Power Universal



BNR 56338, 56348, 56384, 56385, 56386, 56388, 56389, 56396, 56488, 56490

Product Features

- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more
- For daily uncomplicated solutions and quick & easy repairs
- Very good adhesion to all types of surfaces
- Weather-resistant for in-and outdoor applications
- Tearable by hand
- Solvent-free

Product Description

tesa® extra Power Universal is a versatile duct tape with extra bonding power. Ideal for handicrafts, repairing, fastening, bundling and marking and more.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing material	PE-film with PET-filament
Type of adhesive	synthetic rubber
Total thickness	215 µm

Properties/Performance Values

Adhesive strength	High adhesion
Ageing resistance (UV)	yes
Application temperature	from 10 up to 50 °C
Area of use	Outdoor
Hand tearability	yes
Humidity resistance	yes
Oil and grease resistance	yes
Ozone resistance	yes
Residue free removal	no
Solvent free	yes
Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Metal
Tear resistance	yes
Temperature resistance	yes
Temperature resistance max.	95 °C
Tensibility	19 %
Tensile strength	100 N/cm
UV resistant	yes
Water resistance	yes
Waterproof	yes
Writable	no

For latest information on this product please visit
http://l.tesa.com/?ip=56338

Product Information

tesa® extra Power Universal

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit
http://l.tesa.com/?ip=56338