PATRZ KARTA - 2P 10X38MFH30A 600V MIDGET - INDICATOR



Uchwyt bezpiecznika, Niskie napięcie, 32 A, AC 690 V, 10 x 38 mm, 2P, UL, IEC, z sygnalizatorem

Powering Business Worldwide™

Typ	**2P 10X38MFH30A 600V Midget - indicator**
Catalog No.	**CHM2DIU**

Program dostaw

Asortyment			Akcesoria do bezpieczników
Funkcja podstawowa			Oprawa bezpiecznika
Obszar zastosowania			Niskie napięcie
Prąd nominalny	I	A	32
Napięcie nominalne			AC 690 V
Wielkość			10 x 38 mm
Wersja sygnalizatora			z sygnalizatorem
Opis			Montaż szyny DIN oznaczenie kolorystyczne Przeznaczony do użytku z kablem 75°C lub 90°C żyła linkowa końcówki widełkowe z mostkiem grzebieniowym Można używać dowolnego przewodu wysokotemperaturowego o zmniejszonej mocy przyłączeniowej. Modułowy
liczba biegunów			2P
Zastosowanie			do wkładek bezpieczników cylindrycznych do miniaturowych bezpieczników
Standard/znak jakości			UL IEC
Standardy/regulacje			IEC cULus CCC CSA UR

Dane techniczne zgodne z ETIM 6.0

Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse (ecl@ss8.1-27-14-21-21 [ADI305004])			
For fuse size			10x38 mm
Number of poles			2
Concurrently switching N-neutral			No

© 07/2022 by Eaton Industries GmbH