

41452089



SCHUKO soc.out.,mounting orient. var. in 45° steps,screw-in lift term.,R.cl,wh

Technical characteristics

Architecture	
Design	according to DIN 49440
Fixing mode	flush-mounting
Configuration	
Number of modules	1
Main electrical features	
Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A
Electric current	
Rated current	16 A
Dimensions	
Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm
Cover, door	
Cover	Central cover plate
Materials	
Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Material for printing	ASA polar white
Surface appearance	glossy
Metallic colour	No
Installation, mounting	
Installation mode	with spreader claws
Connection	
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1
Type of connection	with screw-in lift terminals
Equipment	
Type of configuration	Laserdruck
Use	
Differentiation characteristic 2 - Sales	Installation position variable in 45° steps

Differentiation characteristic 3 - Sales	17
Safety	
Protection index IP	IP20
Protection	without enhanced contact protection
With enhanced contact protection	No
Identification	
Main design line	Serie R.classic