PCE data sheet

article#	**9250023-p**
article description	**XREEL250 4xSSD54 33m3G1.5H05V GS1**
description long	Cable Reel XREEL250 Reel (black) with central, internal locking mechanism Protected connecting area Solid carrying rack (black) with ergonomic handle and 2 parking positions for the plug Central plate with 4 pcs safety sockets national version with self-closing hinged lids and shutter Rated operating voltage: 250V Rated current: 16A Protection rating: IP54 1 pcs thermal circuit breaker 1 pcs power supply light (green) 33m Black cable H05VV-F 3G1.5mm2 Taurus2 rubber plug 16A 2p+PE 250V IP54 (0511-sr) XREEL250 installed ready for use complies with RoHS directive 2011/65/EU low voltage directive NSpRI 2014/35/EU UV stability according ISO 4892-2 Standard: IEC / EN 61242
GTIN (EAN)	9003399316364
country of origin	PL
customs number	85444290
net weight	4.700 kg
packaging quantitiy	1





ETIM 7.0	EC000191
Housing material	Plastic
Cable assembly	H05VV-F
Core cross section	1.5 mm²
Number of cores	3
Number of socket outlets with protective contact (SCHUKO)	4
Type of mains connection	Protective contact (SCHUKO)
Cable length	33 m
With mounting frame	True
With thermal protection	True
With adjustment	True
Degree of protection (IP rating)	IP54
Colour	Black





www.manufacturer-safety.info

3/8/2021

(C) PC ELECTRIC Ges.m.b.H. - Diesseits 145 - 4973 St. Martin i.l. - Austria - www.pcelectric.at