PATRZ KARTA - Z-MS-40/2



Abbildung ähnlich

Wyłącznik silnikowy 2-biegunowy

Typ	**Z-MS-40/2**
Catalog No.	**248401**
Alternate Catalog No.	**Z-MS-40/2**

Powering Business Worldwide™

Świadectwo typu zgodnie z IEC/EN 61439

Dane techniczne dla zaświadczenia rodzaju konstrukcji			
Znamionowy prąd pracy do podania straty mocy	I_n	A	40
Strata mocy na biegun, w zależności od prądu	P_{vid}	W	3.95
Strata mocy elementu eksploatacyjnego, w zależności od prądu	P_{vid}	W	7.9
Robocza temperatura otoczenia min.		°C	-5
Robocza temperatura otoczenia maks.		°C	50

Dane techniczne zgodne z ETIM 6.0

Low-voltage industrial components (EG000017) / Motor protection circuit-breaker (EC000074)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Motor protection circuit-breaker (ecl@ss8.1-27-37-04-01 [AGZ529013])			
Overload release current setting		A	25 - 40
Adjustment range undelayed short-circuit release		A	400 - 520
Thermal protection			Yes
Phase failure sensitive			No
Switch off technique			Magnetic
Rated operating voltage		V	400 - 400
Rated permanent current Iu		A	40
Rated operation power at AC-3, 230 V		kW	0
Rated operation power at AC-3, 400 V		kW	18.5
Type of electrical connection of main circuit			Screw connection
Type of control element			Rocker lever
Device construction			Complete device in housing
With integrated auxiliary switch			No
With integrated under voltage release			No
Number of poles			2
Rated short-circuit breaking capacity Icu at 400 V, AC		kA	10
Degree of protection (IP)			IP20
Height		mm	75
Width		mm	36
Depth		mm	80

© 07/2022 by Eaton Industries GmbH