Technical Datasheet

ANAMET EUROPE

Galwin 5 - 1046 AW Amsterdam
P.O. Box 8155 - 1005 AD Amsterdam
The Netherlands

Tel.: +31 (0)20 586 3586
Fax: +31 (0)20 688 1126
Email: sales@anamet.nl
Website: www.anametеurope.com

Vat Reg NL001442429B01
Trade register Amsterdam 330 60 401

NUMBER

TDS-3555/A

PRODUCT DESCRIPTION

Ana-Quick fittings for corrugated nylon conduit

PRODUCT RANGE

Ana-Quick product range





ISO straight fitting, male, PA6, colour black, including locknut

THREAD ISO	ANA-QUICK SIZE (DN)	MIN. INTERNAL BORE (MM)	DIMENSIONS IN MM					STANDARD PACKAGE	ARTICLE NUMBER	WEIGHT (KG/100)
			A	B	C	E	F			
M12 x 1,5	7,5	7,5	34	10	17	16	18	50	968.112.1	0,5
M12 x 1,5	10	7,5	36	10	20	18	18	50	968.111.2	0,6
M16 x 1,5	10	11,2	36	10	20	18	22	50	968.115.2	0,7
M16 x 1,5	12	11,2	41	12	23	21	22	50	968.116.2	0,8
M20 x 1,5	12	15,2	41	13	23	21	27	50	968.117.2	1,1
M20 x 1,5	17	15,2	45	13	30	27	27	50	968.120.2	1,4
M25 x 1,5	17	20,0	45	13	30	27	33	20	968.122.2	1,6
M25 x 1,5	23	20,0	48	13	37	34	33	20	968.125.2	2,0
M32 x 1,5	29	26,0	52	15	44	40	41	10	968.132.2	2,8
M40 x 1,5	37	33,5	55	15	52	49	50	8	968.140.2	3,8
M50 x 1,5	50	42,0	55	16	65	62	62	5	968.150.2	5,5
M63 x 1,5	50	52,0	55	16	65	62	74	5	968.160.2	5,8

ANA-QUICK POLYAMIDE FITTINGS

The universal Ana-Quick fitting fits all types of Ana-Quick conduit. The Ana-Quick fitting is easy to connect and due to the integrated release clips also very simple to dis-connect.

Material & Construction:

Construction: 1 piece fitting with integrated release clip and locknut included.
Material: Fitting, clip and locknut are made of halogen free Polyamide PA6.
Temperature: -40°C till +120°C continuous.
Protection class: IP 65 (dust-proof, waterprotected).
Colour: Black.