Socket-outlets

Other socket-outlets



Central plate for USB charger insert

Version	Art. no.
lotus white	**MTN4367-6035**
anthracite	**MTN4367-6034**
sahara	**MTN4367-6033**
stainless steel	**MTN4367-6036**
nickel metallic	**MTN4367-6050**
champagne metallic	**MTN4367-6051**
mocca metallic	**MTN4367-6052**

For System Design.
For the USB charger insert.
To be completed with: USB charger insert MTN4366-0100
USB charger insert 2.4A Type A+C MTN4366-0110



USB charger insert



Version	Art. no.
	MTN4366-0100

USB 2.0 charger with two outputs.
Nominal voltage: AC 100-240 V ± 10 %, 50-60 Hz
Stand by power consumption: < 0.1 W
USB outputs
USB output voltage: DC 5 V ±5 %
Nominal output current: 1x2100 mA
2x1050 mA
USB standard: 2.0
To be completed with: Central plate for USB charger insert System M MTN4367-03.. /04..
System Design MTN4367-60..



USB charger insert 2.4A Type A+C



Version	Art. no.
	MTN4366-0110

USB charger with 1x USB type A output and 1x USB type C output.
For simultaneous operation/ charging of two USB devices with integrated rechargeable battery.
Mains voltage
Nominal voltage: AC 100-240 V ± 10 %, 50-60 Hz
Stand by power consumption: < 0,1 W
USB output
Nominal output voltage: DC 5 V ± 5 %
Nominal output current: 1x2400 mA
2x1200 mA
USB Standard: 2.0
To be completed with: Central plate for USB charger insert System M MTN4367-03.. /04..
System Design MTN4367-60..