EMOS www.emos.eu

Order Code / Item Number | Packaging Type

- tape type: PVC
- width: 19 mm
- length: 20 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10–45 °C
- operating temperature range: -25–90 °C
- ROHS compliant

- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 70 × 20 mm
- packaging: 10 pcs, foil



8 595025 319647

F61921 | 10/10/-/200
20 01 192 010 | 19/20 BILA

- tape type: PVC
- width: 19 mm
- length: 20 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10–45 °C
- operating temperature range: -25–90 °C
- ROHS compliant

- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 70 × 20 mm
- packaging: 10 pcs, foil



8 595025 342409

F61922 | 10/-/-/200
20 01 192 020 | 19/20 CERNA

- tape type: PVC
- width: 19 mm
- length: 20 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10–45 °C
- operating temperature range: -25–90 °C
- ROHS compliant

- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 70 × 20 mm
- packaging: 10 pcs, foil



8 595025 319654

F61923 | 10/10/-/200
20 01 192 030 | 19/20 CERVENA

- tape type: PVC
- width: 19 mm
- length: 20 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10–45 °C
- operating temperature range: -25–90 °C
- ROHS compliant

- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 70 × 20 mm
- packaging: 10 pcs, foil



8 595025 319661

F61924 | 10/10/-/200
20 01 192 040 | 19/20 MODRA

- tape type: PVC
- width: 19 mm
- length: 20 m
- thickness: 0.13 mm
- electric strength - minimum: 40 kV/mm
- flame tests: less than 1 second
- recommended storage temperature: 10–45 °C
- operating temperature range: -25–90 °C
- ROHS compliant

- REACH compliant
- UV resistant
- adhesive material: rubber
- intended use: cable insulation
- dimensions: 70 × 20 mm
- packaging: 10 pcs, foil



8 595025 319678

F61925 | 10/10/-/200
20 01 192 050 | 19/20 ZEL/ZLUTA