MKS1TMK-10		
Operational Frequency		50-60 Hz
Product		Motor Protection Switch
Feature		with Enclosure
Current	**Ie**	25 A
Thermic Current Calibration Interval		6,30-10,0A
Usage Category		AC 3
Mechanical Life	**Min Qty**	100000
Electrical Life	**Min Qty**	100000
Operating Frequency	**On-Off/Hour**	Mek. 360 Elk. 360
Insulation Voltage	**Ui**	690V AC
Impulse Withstand Voltage	**Uimp**	6 kV
Dielectric Strength (Contact-Contact)		1890V
Isolation Resistance		10 MΩ MİN. (500 V DC)
Operating Temperature		-5 / +40 °C
Pollution Degree		3
Protection Degree		IP65
Cable Section		0,75-4 mm²
Screw Torque		1,8 Nm
Short Circuit Breaking Capacity	**Ics**	6 kA
Production Time		Adjustable overload release 13 ranges between 0.1-25 A; Short circuit release factor set at 12xle; Short circuit switching capacity minimum 6 kA / 400 V
Serial		MKS Series
Specifications	Adjustable overload release 13 ranges between 0.1-25 A	
	Short circuit release factor set at 12xle	
	Short circuit switching capacity minimum 6 kA / 400 V	

Standards / Certificates	TS EN 60947-4-1
	