LPSL7

METALOWA GŁOWICA LAMPKI Ø22MM SERII PLATINUM, PRZEZROCZYSTA, BEZ ADAPTERA MONTAŻOWEGO



Przeznaczenie produktu	Głowica lampki sygnalizacyjnej
Seria produktu	LPSL

Charakterystyka ogólna

Kolor	Przezroczysty
Typ pozycji	Pilot light head
Materiał	Stop cynku i aluminium dla części metalowych, poliamid dla części z tworzywa sztucznego
Stopień ochrony według IEC	IP66, IP67 oraz IP69K

Właściwości mechaniczne

Montaż	Bez adaptera montażowego
Adapter do montażu	LPXAU120M

Dane techniczne UL

Stopień ochrony według UL	Typ 1, 2, 3R, 4, 4X, 12, 12K

Warunki otoczenia

Temperatura

Temperatura pracy			
	min.	°C	-25
	maks.	°C	+70
Temperatura składowania			
	min.	°C	-40
	maks.	°C	+85

Wymiary



Certyfikaty i zgodność

Zgodność

- CSA C22.2 n° 14
- IEC/EN/BS 60947-1
- IEC/EN/BS 60947-5-1
- UL508

Certyfikaty

- cULus

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Klasyfikacja ETIM

ETIM 8,0	EC002024 - Akcesoria/części zamienne do aparatury sterowniczej

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding