LPSB6644

METALOWY PRZYCISK Ø22MM SERII PLATINUM, GRZYBKOWY, BLOKOWANY, ODBLOKOWANIE PRZEZ OBRÓT, Ø40MM. DO ZATRZYMANIA AWARYJNEGO. ISO 13850. CZERWONY



Przeznaczenie produktu	Przycisk do zatrzymania awaryjnego (grzybki), blokowany, odblokowanie przez obrót Ø 40 mm/1,6”
Seria produktu	LPSB664

Charakterystyka ogólna

Kolor	Czerwony
Materiał	Stop cynku i aluminium dla części metalowych, poliamid dla części z tworzywa sztucznego
Stopień ochrony według IEC	IP66, IP67 oraz IP69K

Właściwości mechaniczne

Montaż	Bez adaptera montażowego
Adapter do montażu	LPXAU120M

Dane techniczne UL


Stopień ochrony według UL	Typ 1, 2, 3R, 4, 4X, 12, 12K

Warunki otoczenia

Temperatura

Temperatura pracy			
	min.	°C	-25
	maks.	°C	+70
Temperatura składowania			
	min.	°C	-40
	maks.	°C	+85

Wymiary



Certyfikaty i zgodność

Zgodność

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-5-1
UL508

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Certyfikaty

cULus

Klasyfikacja ETIM

ETIM 8,0	EC000221 - Napęd przycisku sterowniczego

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding