

SYMBOL: **4933479684** MANUFACTURER: **Milwaukee** EAN: **4058546374785**

M18 ONEHCCT60-202C - Hydraulic 60 kN cable crimper 18 V, 2.0 Ah, ONE-KEY™, in case, with 2 batteries and charger

- Voltage: 18 V
- Crimping time: 5 s
- Crimping force: 60 kN
- Crimping range: 6 - 300 mm²
- Crimps per battery: >150 on a 50 mm² copper connector
- Vibration level: 0.7 m/s²
- Vibration uncertainty: 1.5 m/s²
- Sound pressure level (LPA): 72.4 dB(A)
- Sound power level (LWA): 83.4 dB(A)
- Battery type: Li-ion
- Weight with battery pack (M18 B2): 3.8 kg

DESCRIPTION

- FORCE LOGIC™ hydraulic cable crimper crimps connectors in less than 5 seconds with 60 kN of force.
- Easy die alignment and linear movement ensure most uniform crimp results.
- Improved ergonomics and slim handle design provide for a comfortable one-handed operation.
- Easy to reach electronic release button within grip area allows users to reset a crimp conveniently at any time.
- The quick latching head is rotatable by 350° and has an integrated light which perfectly illuminates the crimp surface.
- PFM™ (Predictive Force Monitoring): Automatically modifies output based on connector, ensuring optimal pressure every time and visualises with a green light.
- Allows crimping of connectors up to 300 mm² in copper and aluminium.
- Universal die reception is compatible with MILWAUKEE® 22-series die range and most common 60 kN U-dies (C shaped dies) on the market.
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools.
- ONE-KEY™ also features a remote locking functionality. The reporting function delivers a complete tool activity and accuracy protocol.
- Pre-crimp battery check automatically ensures enough charge to complete each crimp.
- Sealed electronics resist harsh environments with dirt, dust and moisture.
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied in case (Kitbox) with 2 batteries and charger.**

FEATURES

Symbol	M18ONEHCCT60-202C
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18