Specyfikacje

Eaton EP-501970

Catalog Number: EP-501970

PV-Surge protection device, 1500V, class 2 tested with AUX contact



General specifications

Product Name
Eaton xPole SPPVR surge protection device

Catalog Number
EP-501970

EAN
9010653062912

Product Length/Depth
104 mm

Product Height
60 mm

Product Width
54 mm

Product Weight
0.31 kg

Compliances
RoHS conform

Certifications
CE

Model Code
SPPVRT2-15-2+PE-AX

Powering Business Worldwide

Elektryczne dane techniczne

Voltage protection level

4.8 KV

Voltage protection level (L-N)

2.5 KV

Nominal voltage at DC

1500 V

Continuous voltage at DC - max

1500 V

PV-voltage - max

1500 V

Nominal discharge surge current (8/20)

20 kA

Discharge surge current (8/20) - max

40 kA

Short-circuit breaking capacity (ISCCR)

9 kA

Signalling at the device

Optic

Mounting method

DIN rail (top hat rail) 35 mm

Number of conductors without earthing

2

Conductor cross section (flexible, fine-strand) - max

25 mm²

Conductor cross section (solid, solid-strand) - max

35 mm²

Conductor cross section (flexible, fine-strand) - min

25 mm²

Conductor cross section (solid, solid-strand) - min

35 mm²

Degree of protection

IP20

Weryfikacja projektu zgodnie z IEC/EN 61439 - dane techniczne

Ambient operating temperature - max

85 °C

Ambient operating temperature - min

-40 °C

Dodatkowe informacje

Features

Category type 2

Fitted with:

Remote signaling contact

Indicator type

Auxiliary Contact

Special features

Pluggable

System configuration type

DC

Do pobrania

Instrukcje montażu

eaton-spd-sppvrt2-xx-2-pe-ax-il235006zu.pdf

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. Wszelkie prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia