EMOS www.emos.eu

Order Code Item Number | Packaging Type

- power: 30 W
- luminous flux: 3 300 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 160 × 110 × 28 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK07
- packaging: 1 pc, box




3 300 lm | 30 W | IP65 | IK07 | NEUTRAL WHITE | 5 YEARS | Quick connector

8 592920 105702

ZS2632 1/-/-/10

15 31 242 632 ZS2632

- power: 50 W
- luminous flux: 5 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 200 × 145 × 28 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK07
- packaging: 1 pc, box




5 500 lm | 50 W | IP65 | IK07 | NEUTRAL WHITE | 5 YEARS | Quick connector

8 592920 105726

ZS2642 1/-/-/10

15 31 242 642 ZS2642

- power: 100 W
- luminous flux: 11 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 300 × 220 × 42 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box




11 000 lm | 100 W | IP65 | IK08 | NEUTRAL WHITE | 5 YEARS | Quick connector

8 592920 105740

ZS2652 1/-/-/5

15 31 242 652 ZS2652

- power: 150 W
- luminous flux: 16 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 335 × 270 × 43 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box




16 500 lm | 150 W | IP65 | IK08 | NEUTRAL WHITE | 5 YEARS | Quick connector

8 592920 105764

ZS2662 1/-/-/3

15 31 242 662 ZS2662

- power: 200 W
- luminous flux: 22 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 390 × 300 × 49 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box




22 000 lm | 200 W | IP65 | IK08 | NEUTRAL WHITE | 5 YEARS | Quick connector

8 592920 105788

ZS2672 1/-/-/2

15 31 242 672 ZS2672