Luminaires for special applications

ORIENTATION LUMINAIRES

AMAL

CLASSIC


ZC0108


ZC0110


ZC0109


ZC0111

see page 132

DIRAL

CLASSIC


ZC0105


ZC0106

see page 133

DIRBY

CLASSIC


ZC0114


ZC0116


ZC0117

see page 134

AMAL

AMAL orientation luminaires in brushed aluminium are designed for recessed mounting. The aluminium body and glass milk diffuser guarantee a superior service life.

Main benefits:
- minimal power consumption
- IP65 rating ensures water resistance
- in neutral or warm white

Areas of use: in the household and industrial spaces, for staircase lighting, house facades, walls etc.

Lifetime	30 000 hours
CRI	> 80
Body material	aluminium
Diffuser material	glass
IP	IP65













ZC0108
1/-/-/24

ZC0110
1/-/-/24

ZC0109
1/-/-/24

ZC0111
1/-/-/24

Type	EAN	Power	Luminous Flux	CCT	PF	Luminous Efficacy	Through-Wiring	W × H × D
ZC0108	8592920037348	1.5 W	55 lm	3 000 K	> 0.5	37 lm/W	yes	123 × 53 × 61 mm
ZC0109	8592920037355	1.5 W	75 lm	3 000 K	> 0.5	50 lm/W	yes	80 × 80 × 61 mm
ZC0110	8592920054789	1.5 W	55 lm	4 000 K	> 0.5	37 lm/W	yes	123 × 53 × 61 mm
ZC0111	8592920054796	2 W	70 lm	4 000 K	> 0.5	50 lm/W	yes	80 × 80 × 61 mm