Product data sheet

Specifications



switch-disconnector fuse body GS1 3 poles - UL 60 A - fuse size J

GS1GU3

Discontinued

Main

Range of Product	TeSys GS
Range	TeSys
Device short name	GS1G
Fuse type	UL
Fuse size	J
Product or Component Type	Fuse switch disconnector body
Device Application	Distribution
Poles description	3P
Network type	DC AC
Type of operating handle	Front

Complementary

Network Frequency	50/60 Hz
Mounting Support	Rail Plate
[Ie] rated operational current	60 A
Rated operational power in W	30 W 400 V AC-23)
Product Weight	4.9 lb(US) (2.2 kg)

Environment

Standards	CSA UL
Product Certifications	LROS (Lloyds register of shipping) LOVAG ASEFA
IP degree of protection	IP20 IEC 60529 with terminal cover)

Ordering and shipping details

Category	22640-IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	00785901179573
Returnability	No

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Country of origin	TN

Contractual warranty

Warranty	18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

EU RoHS Directive	**Compliant**
California proposition 65	**WARNING: Cancer - www.P65Warnings.ca.gov**