

Material cable sheath	PVC
Cable sheath diameter (approx.)	4.9 mm
max. bandwidth	100 MHz
Cable type	round cable
Inner conductor material	CCA (copper-clad aluminium)
AWG	26/7 (stranded)
Shielding class	U/UTP
Connection, type	RJ45 male 90° (8P8C)
Connection 2, type	RJ45 male (8P8C)
Connection, shielding	no
Latch protection	unilaterally

Goobay

CAT 5e patchcable 1x 90°angled, U/UTP

CCA

- unshielded LAN/network cable to connect network components with 2 x RJ45 connectors
- ideal solution with minimal space
- with 3µ gold plated PINs
- slimline strain relief
- Latch protection and length specification on straight plug
- pair-sequence acc. to EIA/TIA 568B







Cable length	black	white
	Bulk	Bulk
0.25 m	94169	94161
0.50 m	94170	94162
1.00 m	94171	94163
2.00 m	94172	94164
3.00 m	94173	94165
5.00 m	94174	94166
10.00 m	94175	94167
15.00 m	94193	94168



Material cable sheath	PVC
Cable sheath diameter (approx.)	5.9 mm
max. bandwidth	100 MHz
Cable type	round cable
Inner conductor material	CU (copper)
AWG	26/7 (stranded)
Shielding class	F/UTP
Number of shieldings	1 x
Type 1, shielding	foil (aluminum)
Connection, type	RJ45 male (8P8C)
Connection 2, type	RJ45 male (8P8C)
Connection, shielding	yes
Latch protection	unilaterally

Goobay

CAT 5e extension cable F/UTP, black

RJ45 male (8P8C) > RJ45 female (8P8C)

- shielded network cable extension for extending your network components
- outer shield: foil screening
- molded RJ45 socket
- with 3µ gold plated PINs
- with length indication on the slimline strain relief (plug only)
- plug with latch protection
- pin out: 1:1, pair-sequence acc. to EIA/TIA 568B



Cable length	Bulk
0.50 m	73386
1.00 m	91886
1.50 m	73387
2.00 m	73388
3.00 m	91883
5.00 m	91884
7.50 m	73389
10.00 m	91885
15.00 m	73390