

Material cable sheath	PVC
Cable sheath diameter (approx.)	5.9 mm
max. bandwidth	250 MHz
Cable type	round cable
Inner conductor material	CCA (copper-clad aluminium)
AWG	27/7 (stranded)
Shielding class	S/FTP (PiMF)
Number of shieldings	2 x
Type 1, shielding	foil (alu) PiMF
Type 2, shielding	braid (alu) overall shield
Connection, type	RJ45 male (8P8C)
Connection, shielding	yes
Latch protection	both sides

Goobay

CAT 6 patch cable S/FTP (PiMF)

CCA

- double shielded LAN/network cable to connect network components with 2 x RJ45 connectors
- with 3µ gold plated PINs
- pairs screening: PIMF (pairs in metal foil) + outer shield: braiding
- with length indication on the slimline strain relief
- with latch protection
- pair-sequence acc. to EIA/TIA 568B
- suitable for Gigabit (10/100/1000 Mbit)





Cable length	grey	black	white	blue	orange	yellow	green	magenta	red	violet	transparent
	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk
0.25 m	93371	95458	95461	95452	95456	95453	95454	95455	95457	95460	95459
0.50 m	93568	95468	95471	95462	95466	95463	95464	95465	95467	95470	95469
1.00 m	93569	95478	95481	95472	95476	95473	95474	95475	95477	95480	95479
1.50 m	95567	95572	95575	95565	95570	95566	95568	95569	95571	95574	95573
2.00 m	93570	95498	95501	95492	95496	95493	95494	95495	95497	95500	95499
3.00 m	93571	95508	95511	95502	95506	95503	95504	95505	95507	95510	95509
5.00 m	93572	95518	95521	95512	95516	95513	95514	95515	95517	95520	95519
7.50 m	93650	95528	95531	95522	95526	95523	95524	95525	95527	95530	95529
10.00 m	93651	95488	95491	95482	95486	95483	95484		95487	95490	95489



Material cable sheath	LSZH
Cable sheath diameter (approx.)	5.8 mm
max. bandwidth	250 MHz
Cable type	round cable
Inner conductor material	CU (copper)
AWG	26/7 (stranded)
Shielding class	U/UTP
Connection, type	RJ45-Stecker (8P8C)
Connection, shielding	no
Latch protection	both sides

Goobay

CAT 6, U/UTP patch cable, LSZH, CU, grey

LSZH halogen-free, CU

- unshielded LAN/network cable to connect network components with 2 x RJ45 connectors
- with 3µ gold plated PINs
- with length indication on the strain relief
- with latch protection
- pair-sequence acc. to EIA/TIA 568B
- suitable for Gigabit (10/100/1000 Mbit)



Cable length	Bulk
0.50 m	93668
1.00 m	93669
1.50 m	93670
2.00 m	93671
3.00 m	93672

Cable length	Bulk
5.00 m	93673
7.50 m	93674
10.00 m	93675
15.00 m	93689
20.00 m	93690