

Material cable sheath	PVC
height of cable sheath	1.5 mm
width of cable sheath	6 mm
max. bandwidth	500 MHz
Cable type	flat cable
Inner conductor material	CU (copper)
AWG	32/7 (stranded)
Shielding class	U/UTP
Connection, type	RJ45 male (8P8C)
Latch protection	no





Goobay

CAT 6a flat-patch cable U/UTP

copper

- unshielded flat LAN/network cable to connect network components with 2 x RJ45 connectors
- Low bending radius, extremly flexible, ideal to move to save space behind baseboards
- OD only 1.5 x 6 mm
- with 3µ gold plated contacts (PINs)
- short connector type without latch protection
- slimline strain relief
- pair-sequence acc. to EIA/TIA 568B





Cable length	black	white	blue	orange	dark brown	yellow	green	light brown	magenta	red	violet
	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk
0.50 m	96301	96303	96295	96299	96304	96296	96297	96305	96298	96300	96302
1.00 m	96312	96314	96306	96310	96315	96307	96308	96316	96309	96311	96313
2.00 m	96323	96325	96317	96321	96326	96318	96319	96327	96320	96322	96324
3.00 m	96334	96336	96328	96332	96337	96329	96330	96338	96331	96333	96335
5.00 m	96345	96347	96339	96343	96348	96340	96341	96349	96342	96344	96346
7.00 m	96356	96358	96350	96354	96359	96351	96352	96360	96353	96355	96357
10.00 m	96367	96369	96361	96365	96370	96362	96363	96371	96364	96366	96368
15.00 m	96378	96380	96372	96376	96381	96373	96374	96382	96375	96377	96379
20.00 m	96389	96391	96383	96387	96392	96384	96385	96393	96386	96388	96390