SIEMENS

## Data sheet 6AV2123-3GB32-0AW0




SIMATIC HMI MTP700, Unified Basic Panel, touch operation, 7" widescreen TFT display, 16 million colors, PROFINET interface, configurable as of WinCC Unified Basic V18 Update 3, contains open-source software, which is provided free of charge see enclosed Blu-ray

| | |
|---|---|
| **General information** | |
| Product type designation | MTP700 Unified Basic |
| **Display** | |
| Design of display | TFT |
| Screen diagonal | 7 in |
| Display width | 152.4 mm |
| Display height | 91.4 mm |
| Number of colors | 16 777 216 |
| Resolution (pixels) | |
| ● Horizontal image resolution | 800 pixel |
| ● Vertical image resolution | 480 pixel |
| Backlighting | |
| ● MTBF backlighting (at 25 °C) | 20 000 h; At 25°C |
| ● Backlight dimmable | Yes; 10 ... 100% |
| **Control elements** | |
| Keyboard | |
| ● Numeric keyboard | Yes; Onscreen keyboard |
| ● alphanumeric keyboard | Yes; Onscreen keyboard |
| Touch operation | |
| ● Design as touch screen | Yes |
| ● Design as multi-touch screen | Yes |
| ● Monitor keyboard | Yes |
| **Installation type/mounting** | |
| Mounting position | vertical |
| Mounting in portrait format possible | Yes |
| Mounting in landscape format possible | Yes |
| maximum permissible angle of inclination without external ventilation | 35° |
| **Supply voltage** | |
| Type of supply voltage | DC |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| **Input current** | |
| Current consumption (rated value) | 0.2 A |
| current consumption (for rated value of supply voltage), min. | 0.16 A |
| current consumption (for rated value of supply voltage), max. | 0.51 A |
| Current consumption, max. | 0.69 A; at 19.2 V |
| Starting current inrush I²t | 0.36 A²·s |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| **Power** | |
| Active power input, typ. | 8.2 W |
| **Processor** | |
| Processor type | ARM |
| **Storage** | |
| Flash | Yes |
| RAM | Yes |
| **Type of output** | |
| Acoustics | |
| ● Buzzer | No |
| ● Speaker | No |
| **Time of day** | |
| Clock | |
| ● Hardware clock (real-time) | Yes |
| ● Software clock | Yes |
| ● retentive | Yes; Back-up duration typically 6 weeks |
| ● synchronizable | Yes |
| **Interfaces** | |
| Number of industrial Ethernet interfaces | 1; Gigabit Ethernet (IE/PN), RJ45 |
| Number of RS 485 interfaces | 0 |
| Number of RS 422 interfaces | 0 |
| Number of USB interfaces | 2; USB 2.0 |
| Number of SD card slots | 0 |
| Industrial Ethernet | |
| ● Industrial Ethernet status LED | 2 |
| ● Number of ports of the integrated switch | 1 |
| **Protocols** | |
| PROFINET | Yes |
| Supports protocol for PROFINET IO | No |
| IRT | No |
| MPI | No |
| Protocols (Ethernet) | |
| ● TCP/IP | Yes |
| ● DHCP | Yes |
| ● SNMP | Yes |
| ● DCP | Yes |
| ● LLDP | Yes |
| Redundancy mode | |
| Media redundancy | |
| — MRP | No |
| Further protocols | |
| ● CAN | No |
| **EMC** | |
| Emission of radio interference acc. to EN 55 011 | |
| ● Limit class A, for use in industrial areas | Yes |
| ● Limit class B, for use in residential areas | No |
| **Degree and class of protection** | |
| IP (at the front) | IP65 |
| IP (rear) | IP20 |
| NEMA (front) | NEMA 4, NEMA 4x (when installed) |
| ● Enclosure Type 4 at the front | Yes |
| ● Enclosure Type 4x at the front | Yes |
| ● Enclosure Type 12 at the front | No |
| **Standards, approvals, certificates** | |
| CE mark | Yes |
| UKCA mark | Yes |
| cULus | Yes |
| FM approval | No |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| EAC (formerly Gost-R) | No |
| CCC | No |
| Ecological footprint | |
| ● environmental product declaration | Yes |
| Global warming potential | |
| — global warming potential, (total) [CO2 eq] | 162 kg |
| — global warming potential, (during production) [CO2 eq] | 23.7 kg |
| — global warming potential, (during operation) [CO2 eq] | 139 kg |
| — global warming potential, (after end of life cycle) [CO2 eq] | -1.23 kg |
| Use in hazardous areas | |
| ● ATEX Zone 2 | No |
| ● ATEX Zone 22 | No |
| ● IECEx Zone 2 | No |
| ● IECEx Zone 22 | No |
| ● cULus Class I Zone 2, Division 2 | No |
| ● cULus Class II Division 2 | No |
| ● FM Class I Division 2 | No |
| ● FM Class II Division 2 | No |
| Marine approval | |
| ● Germanischer Lloyd (GL) | No; included in DNV |
| ● American Bureau of Shipping (ABS) | Yes; in preparation |
| ● Bureau Veritas (BV) | Yes; in preparation |
| ● Det Norske Veritas (DNV) | Yes |
| ● Korean Register of Shipping (KRS) | Yes |
| ● Lloyds Register of Shipping (LRS) | Yes |
| ● Nippon Kaiji Kyokai (Class NK) | Yes |
| ● Chinese Classification Society (CCS) | Yes |
| **Ambient conditions** | |
| Suited for indoor use | Yes |
| Suited for outdoor use | No |
| Ambient temperature during operation | |
| Operation (vertical installation) | |
| — For vertical installation, min. | 0 °C |
| — For vertical installation, max. | 50 °C |
| Operation (max. tilt angle) | |
| — At maximum tilt angle, min. | 0 °C |
| — At maximum tilt angle, max. | 40 °C |
| Operation (vertical installation, portrait format) | |
| — For vertical installation, min. | 0 °C |
| — For vertical installation, max. | 40 °C |
| Operation (max. tilt angle, portrait format) | |
| — At maximum tilt angle, min. | 0 °C |
| — At maximum tilt angle, max. | 35 °C |
| Ambient temperature during storage/transportation | |
| ● min. | -20 °C |
| ● max. | 60 °C |
| Relative humidity | |
| ● Operation, max. | 90 %; no condensation |
| **Operating systems** | |
| proprietary | Yes |
| **Configuration** | |
| Message indicator | Yes |
| Alarm system (incl. buffer and acknowledgment) | Yes |
| Recipe management | Yes |
| Configuration software | |


© Copyright Siemens

| | |
|---|---|
| ● WinCC Advanced (TIA Portal) | Yes |
| ● WinCC Professional (TIA Portal) | Yes |
| ● WinCC Unified Basic Engineering (TIA Portal) | Yes |
| ● WinCC Unified Comfort Engineering (TIA Portal) | Yes |
| ● WinCC Unified PC Engineering (TIA Portal) | Yes |
| **Languages** | |
| Online languages | |
| ● Number of online/runtime languages | 32 |
| Project languages | |
| ● Languages per project | 32 |
| **Functionality under WinCC Unified** | |
| Libraries | Yes |
| Applications/options | No |
| Number of Visual Basic Scripts | No |
| JavaScript | Yes |
| Task planner | |
| ● time-controlled | Yes |
| ● task-controlled | Yes |
| Help system | |
| ● Number of characters per info text | 70 |
| ● Number of message texts per message | 10 |
| Message system | |
| ● Number of alarm classes | 32 |
| ● Bit messages | |
| — Number of bit messages | 2 000 |
| ● Analog messages | |
| — Number of analog messages | 100 |
| ● S7 alarm number procedure | Yes |
| ● System messages HMI | Yes |
| ● System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ... ) | Yes |
| ● Number of characters per message | 512 |
| ● Number of process values per message | 10 |
| ● Acknowledgment groups | Yes |
| ● Message indicator | No |
| ● Message buffer | Yes; Configured as alarm archive |
| — Circulating buffer | Yes |
| — retentive | Yes |
| — maintenance-free | Yes |
| Parameter set management (recipes) | |
| ● Number of parameter set types | 250 |
| ● Parameter sets per parameter set type | 250 |
| ● Entries per parameter set | 250 |
| ● Size of internal parameter set memory | 5 Mbyte |
| ● Parameter set memory expandable | Yes |
| Variables | |
| ● Number of variables per device | 1 000 |
| ● Number of variables per screen | 300 |
| ● Limit values | Yes |
| ● Structures | Yes |
| ● Arrays | Yes |
| Images | |
| ● Number of configurable images | 300 |
| ● Faceplate | Yes |
| Image objects | |
| ● Number of objects per image | 600 |
| ● Picture window | Yes |
| ● Text fields | Yes |
| ● I/O fields | Yes |


© Copyright Siemens

| | |
|---|---|
| ● Graphic I/O fields (graphics list) | Yes |
| ● Symbolic I/O fields (text list) | Yes |
| ● Scalable Vector Graphics (SVG) | Yes |
| ● Date/time fields | Yes |
| ● Checkbox | Yes |
| ● Option button | Yes |
| ● Switches | Yes |
| ● Buttons | Yes |
| ● Graphic display | Yes |
| ● Icons | Yes |
| ● Custom web display | No |
| ● Geometric objects | Yes |
| Complex image objects | |
| ● Number of complex objects per screen | 5 |
| ● Alarm view | Yes |
| ● Trend view | Yes |
| ● User view | Yes |
| ● Status/control | Yes |
| ● Parameter set display | Yes |
| ● HTML browser | Yes |
| ● Bar graphs | Yes |
| ● Sliders | Yes |
| ● Pointer instruments | Yes |
| ● Analog/digital clock | Yes |
| Lists | |
| ● Number of text lists per project | 300 |
| ● Number of entries per text list | 250 |
| ● Number of graphics lists per project | 100 |
| ● Number of entries per graphics list | 250 |
| Archiving | |
| ● Number of archives per device | 10 |
| ● Number of entries per archive | 50 000 |
| ● Message archive | Yes |
| ● Process value archive | Yes |
| ● Archiving methods | |
| — Sequential archive | Yes |
| — Short-term archive | Yes |
| ● Memory location | |
| — Memory card | No |
| — USB memory | Yes |
| — Ethernet | No |
| Security | |
| ● Number of roles | 50 |
| ● Number of function rights | 20; V18 |
| ● Number of users | 200 |
| ● Password export/import | Yes |
| ● Central user administration | Yes |
| Transfer (upload/download) | |
| ● USB | Yes |
| ● Ethernet | Yes |
| ● using external storage medium | Yes |
| Process coupling | |
| ● S7-1200 | Yes |
| ● S7-1500 | Yes |
| ● S7-200 | No |
| ● S7-300/400 | Yes |
| ● Number of S7 connections | 8 |
| ● LOGO! | Yes; as of WinCC Unified V20 |
| ● SIMOTION | No |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| ● OPC UA Client | Yes |
| ● OPC UA Server | No |
| ● Software Controller/Open Controller | No |
| Service tools/configuration aids | |
| ● Backup/Restore manually | Yes |
| ● Backup/Restore automatically | No |
| ● Simulation | Yes |
| ● Device switchover | Yes |
| **Peripherals/Options** | |
| Peripherals | Barcode reader |
| Printer | No |
| SIMATIC HMI MM memory card: Multi Media Card | No |
| SIMATIC HMI SD memory card: Secure Digital memory card | No |
| SIMATIC HMI CF memory card Compact Flash Card | No |
| USB memory | Yes |
| SIMATIC IPC USB Flashdrive (USB stick) | Yes |
| SIMATIC HMI USB stick | Yes |
| Network camera | No |
| **Mechanics/material** | |
| Enclosure material (front) | |
| ● Plastic | Yes |
| **Dimensions** | |
| Width of the housing front | 214 mm |
| Height of housing front | 158 mm |
| Mounting cutout, width | 197 mm |
| Mounting cutout, height | 141 mm |
| mounting depth | 36 mm |
| **Weights** | |
| Weight (without packaging) | 0.85 kg |
| Weight (with packaging) | 1.1 kg |

**Classifications**

| | Version | Classification |
|---|---|---|
| eClass | 14 | 27-33-02-01 |
| eClass | 12 | 27-33-02-01 |
| eClass | 9.1 | 27-33-02-01 |
| eClass | 9 | 27-33-02-01 |
| eClass | 8 | 27-24-23-02 |
| eClass | 7.1 | 27-24-23-02 |
| eClass | 6 | 27-24-23-02 |
| ETIM | 10 | EC001412 |
| ETIM | 9 | EC001412 |
| ETIM | 8 | EC001412 |
| ETIM | 7 | EC001412 |

**Approvals / Certificates**

| General Product Approval | Maritime application |
|---|---|

**Maritime application**


Subject to change without notice
© Copyright Siemens

| | | | | | |
|---|---|---|---|---|---|
| | DNV | LRS | NK / Nippon Kaiji Kyokai | RINA | CCS (China Classification Society) |

| Maritime application | Environment |
|---|---|
| KR (Korean Register of Shipping) | |

**last modified:** 4/1/2025


Subject to change without notice
© Copyright Siemens