Specyfikacje



Eaton 265226

Z-R230/4S. Installation relay, 230VAC/50Hz, 4N/O, 20A, 2HP

Specyfikacje ogólne	
PRODUCT NAME	Eaton distribution board accessory
CATALOG NUMBER	265226
EAN	4015082652265
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	70 mm
PRODUCT WIDTH	35 mm
PRODUCT WEIGHT	0.263 kg
COMPLIANCES	RoHS conform CE Marked
MODEL CODE	Z-R230/4S

Powering Business Worldwide

Specyfikacje produktu

AMPERAGE RATING	20 A
MOUNTING METHOD	DIN rail
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	10.4 W
CONTROL VOLTAGE 1 TYPE	AC
AMBIENT OPERATING TEMPERATURE - MAX	45 °C
AMBIENT OPERATING TEMPERATURE - MIN	-20 °C
CONTROL VOLTAGE 1 - MAX	230 V
CONTROL VOLTAGE 1 - MIN	230 V
CONTROL VOLTAGE 2 - MAX	0 V
CONTROL VOLTAGE 2 - MIN	0 V
FREQUENCY CONTROL VOLTAGE 1 - MAX	50 Hz
FREQUENCY CONTROL VOLTAGE 1 - MIN	50 Hz
FREQUENCY CONTROL VOLTAGE 2 - MAX	0 Hz
FREQUENCY CONTROL VOLTAGE 2 - MIN	0 Hz
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	2 W
INCANDESCENT LAMP LOAD - MAX	0 W
LOAD FLUORESCENT LAMP - MAX	0 VA
LOAD FLUORESCENT LAMP (DUO CIRCUIT) - MAX	0 VA
LOAD FLUORESCENT LAMP (PARALLEL COMPENSATED) - MAX	0 VA
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	4

Do pobrania

	122I163
RYSUNKI	eaton-mcb-dimensions-122x137.eps

CONTROL VOLTAGE 2 TYPE	AC/DC
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	20 A
SUPPLY VOLTAGE - MAX	250 V
SUPPLY VOLTAGE - MIN	250 V
SWITCHING CURRENT (COS PHI = 0.6) - MAX	0 A
WIDTH IN NUMBER OF MODULAR SPACINGS	2
BUILT-IN DEPTH	60 mm
VOLTAGE TYPE	AC
FUNCTIONS	Mechanical

NAZWA PROJEKTU:	
NUMER PROJEKTU:	
PRZYGOTOWANE PRZEZ:	
DATA:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2026 Eaton. Wszelkie prawa zastrzeżone.

Najnowsze informacje o produktach i wsparciu znajdują się na naszych mediach społecznościowych.