Specyfikacje



Eaton 112004

Eaton Moeller series Power Defense - Molded Case Circuit Breaker. Switch-disconnector, 3 p, 250A, frame size 2

Specyfikacje ogólne	
PRODUCT NAME	Eaton Moeller series Power Defense molded case switch-disconnector
CATALOG NUMBER	112004
EAN	4015081115525
PRODUCT LENGTH/DEPTH	142 mm
PRODUCT HEIGHT	185 mm
PRODUCT WIDTH	105 mm
PRODUCT WEIGHT	2.15 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC
MODEL CODE	LN2-250-I

Powering Business Worldwide

Dodatkowe informacje

FUNCTIONS	Disconnectors/main switches Interlockable Voltage release optional

Dostawy

AMPERAGE RATING	250 A
APPLICATION	Use in unearthed supply systems at 690 V
CIRCUIT BREAKER FRAME TYPE	LN2
FEATURES	Version as emergency stop installation Version as main switch Motor drive optional Version as maintenance-/service switch
NUMBER OF POLES	Three-pole
SPECIAL FEATURES	Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113. Isolating characteristics to IEC/EN 60947-3 and VDE 0660. Busbar tag shroud to VDE 0160 Part 100. Rated current = rated uninterrupted current: 250 A
TYPE	Switch-disconnector

Weryfikacja projektu zgodnie z normą IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.

Weryfikacja projektu zgodnie z IEC/EN 61439 - dane techniczne

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	48 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	250 A

10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

AMPERAGE RATING	250 A
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
HANDLE TYPE	Rocker lever
LIFESPAN, ELECTRICAL	5000 operations at 690 V AC-3 10000 operations at 400 V AC-1 7500 operations at 690 V AC-1 10000 operations at 415 V AC-1 7500 operations at 400 V AC-3 7500 operations at 415 V AC-3
NUMBER OF OPERATIONS PER HOUR - MAX	120
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	100 kA
RATED CONDITIONAL SHORT-CIRCUIT CURRENT WITH BACK-UP FUSE	100 kA at 400/415 V PN2(N2)-160...250: 250 AgGgL 80 kA at 690 V
RATED CONDITIONAL SHORT-CIRCUIT CURRENT WITH DOWNSTREAM FUSE	80 kA at 690 V PN2(N2)-160...250: 250 AgGgL 100 kA at 400/415 V
RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT AUXILIARY CONTACTS	6000 V
RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT MAIN CONTACTS	8000 V
RATED INSULATION VOLTAGE (UI)	690 V
RATED OPERATING FREQUENCY	50 Hz
RATED OPERATING POWER AT AC-23, 400 V	132 kW
RATED OPERATING POWER AT AC-3, 400 V	0 kW
RATED OPERATING	400 V

Technical data - mechanical

DEGREE OF PROTECTION (IP), FRONT SIDE	IP20
HANDLE COLOR	Gray
LIFESPAN, MECHANICAL	20000 operations
MOUNTING METHOD	Built-in device fixed built-in technique Ground mounting Fixed Distribution board installation Intermediate mounting
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
SPECIAL FEATURES	Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113. Isolating characteristics to IEC/EN 60947-3 and VDE 0660. Busbar tag shroud to VDE 0160 Part 100. Rated current = rated uninterrupted current: 250 A
SWITCH POSITIONS	I, +, 0

VOLTAGE (UE) AT AC - MAX	
RATED OPERATIONAL CURRENT	250 A (690 V AC-22/23A, making and breaking capacity) 250 A (415 V AC-1, making and breaking capacity) 250 A (690 V AC-1, making and breaking capacity) 250 A (415 V AC-22/23A, making and breaking capacity)
RATED PERMANENT CURRENT AT AC-21, 400 V	0 A
RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 690 V, 50/60 HZ	5.5 kA
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	3.5 kA
RATED SHORT-TIME WITHSTAND CURRENT (T = 0.3 S)	3.5 kA
RATED SHORT-TIME WITHSTAND CURRENT (T = 1 S)	3.5 kA
SHORT-CIRCUIT PROTECTIVE DEVICE FUSES - MAX	250 A gL
SHORT-CIRCUIT TOTAL BREAKTIME	< 10 ms
SWITCHING POWER AT 400 V	0 kW
VOLTAGE RATING	690 V - 690 V

Technical data - mechanical - terminals

STANDARD TERMINALS	Screw terminal
TERMINAL CAPACITY (ALUMINUM SOLID CONDUCTOR/CABLE)	16 mm² (1x) at tunnel terminal
TERMINAL CAPACITY (ALUMINUM STRANDED CONDUCTOR/CABLE)	25 mm² - 185 mm² (1x) at tunnel terminal
TERMINAL CAPACITY (CONTROL CABLE)	0.75 mm² - 1.5 mm² (2x) 0.75 mm² - 2.5 mm² (1x)
TERMINAL CAPACITY (COPPER BUSBAR)	Min. 16 mm x 5 mm direct at switch rear-side connection M8 at rear-side screw connection Max. 20 mm x 5 mm direct at switch rear-side connection
TERMINAL CAPACITY (COPPER SOLID CONDUCTOR/CABLE)	4 mm² - 16 mm² (2x) direct at switch rear-side connection 16 mm² - 185 mm² (1x) at tunnel terminal 4 mm² - 16 mm² (1x) at box terminal 4 mm² - 16 mm² (2x) at box terminal 4 mm² - 16 mm² (1x) direct at switch rear-side connection
TERMINAL CAPACITY (COPPER STRANDED CONDUCTOR/CABLE)	25 mm² - 185 mm² (1x) direct at switch rear-side connection 25 mm² - 70 mm² (2x) direct at switch rear-side connection 25 mm² - 185 mm² (1x) at box terminal 25 mm² - 185 mm² (1x) at tunnel terminal 25 mm² - 70 mm² (2x) at box terminal
TERMINAL CAPACITY (COPPER STRIP)	Min. 2 segements of 16 mm x 0.8 mm at rear-side connection (punched) Max. 10 segments of 16 mm x 0.8 mm at box terminal Max. 10 segments of 16 mm x 0.8 mm at rear-side connection (punched) Min. 2 segments of 9 mm x 0.8 mm at box terminal

Do pobrania

DEKLARACJE ZGODNOŚCI	eaton-molded-case-switch-disconnector-declaration-of-conformity-eu250138en.pdf
INSTRUKCJE MONTAŻU	eaton-circuit-breaker-basic-unit-lzm2-il01206012z.pdf
MODELE MCAD	DA-CD-nzm2_3p eaton-molded-case-switches-mcad-drawings-nzm2-3p.dwg eaton-molded-case-switches-mcad-3d-models-nzm2-3p.stp DA-CS-nzm2_3p
RYSUNKI	eaton-circuit-breaker-switch-nzm-mccb-dimensions-017.eps eaton-circuit-breaker-nzm-mccb-dimensions-019.eps eaton-circuit-breaker-switch-nzm-mccb-3d-drawing.eps

NAZWA PROJEKTU:	
NUMER PROJEKTU:	
PRZYGOTOWANE PRZEZ:	
DATA:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2026 Eaton. Wszelkie prawa zastrzeżone.

Najnowsze informacje o produktach i wsparciu znajdują się na naszych mediach społecznościowych.