Specyfikacje



Zdjęcie jest reprezentatywne



Eaton 278483

Eaton Moeller® series PKZM01 Motor-protective circuit-breaker, 440 V: 3 kW, Ir = 4 - 6.3 A, IP20

Specyfikacje ogólne	
PRODUCT NAME	Eaton Moeller® series PKZM01 Motor-protective circuit-breaker
CATALOG NUMBER	278483
EAN	4015082784836
PRODUCT LENGTH/DEPTH	93 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.3 kg
CERTIFICATIONS	IEC/EN 60947 UL File No.: E36332 UL 60947-4-1 UL Category Control No.: NLRV CSA CSA Class No.: 3211-05 CSA File No.: 165628 VDE 0660 IEC/EN 60947-4-1 CE CSA-C22.2 No. 60947-4-1-14 UL
MODEL CODE	PKZM01-6,3

Powering Business Worldwide

Klimatyczne warunki otoczenia

ALTITUDE	Max. 2000 m
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Weryfikacja projektu konstrukcji

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	6.3 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product

	standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	5.68 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.89 W

Dane elektryczne

RATED FREQUENCY - MAX	60 Hz
RATED FREQUENCY - MIN	50 Hz
RATED OPERATIONAL CURRENT (IE)	6.3 A
RATED OPERATIONAL POWER AT AC-3E, 220/230 V, 50 HZ	1.1 kW
RATED OPERATIONAL POWER AT AC-3E, 380/400 V, 50 HZ	2.2 kW
RATED OPERATIONAL POWER AT AC-3E, 440 V, 50 HZ	3 kW
RATED OPERATIONAL VOLTAGE (UE) - MAX	440 V
RATED OPERATIONAL VOLTAGE (UE) - MIN	440 V
RATED UNINTERRUPTED CURRENT (IU)	6.3 A

Features & functions

ACTUATOR TYPE	Push button
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
FUNCTIONS	Phase failure sensitive Motor protection
NUMBER OF POLES	Three-pole

Informacje ogólne

CONNECTION	Screw terminals
DEGREE OF PROTECTION	Terminals: IP00 IP20
LIFESPAN, ELECTRICAL	50,000 operations (at 400V, AC-3)
LIFESPAN, MECHANICAL	50,000 Operations (Main conducting paths)
MOUNTING POSITION	Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.
OPERATING FREQUENCY	25 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Motor protective circuit breaker
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
SUITABLE FOR	Branch circuit: Manual type E if used with terminal, or suitable for group installations, (UL/CSA) Also motors with efficiency class IE3
TEMPERATURE COMPENSATION	≤ 0.25 %/K, residual error for T > 40° -25 - 55 °C, Operating range -5 - 40 °C to IEC/EN 60947, VDE 0660

Moc znamionowa silnika

ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE	0.25 HP
ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE	1 HP
ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE	0.5 HP
ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE	1.5 HP
ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	3 HP
ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE	5 HP

Wytrzymałość zwarciowa

RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 400 V AC	50 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 440 V AC	50 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 400 V AC	50 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 440 V AC	50 kA
SHORT-CIRCUIT CURRENT	60 kA DC, up to 250 V DC, Main conducting paths
SHORT-CIRCUIT CURRENT RATING (GROUP PROTECTION)	50 kA, 600 V High Fault, Fuse, SCCR (UL/CSA) with 600 A, 600 V High Fault, Fuse, SCCR (UL/CSA) 50 kA, 600 V High Fault, CB, SCCR (UL/CSA) with 600 A, 600 V High Fault, CB, SCCR (UL/CSA)
SHORT-CIRCUIT RELEASE	Basic device fixed 15.5 x Iu ± 20% tolerance 97.7 A, Irm

Zdolność przełączania

SWITCHING CAPACITY	6.3 A (3 contacts in series), DC-5 up to 250V 6.3 A, AC-3 up to 440 V

Przekroje poprzeczne

STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (1 - 6) mm², ferrule to DIN 46228 1 x (1 - 6) mm², ferrule to DIN 46228
TERMINAL CAPACITY (SOLID)	1 x (1 - 6) mm² 2 x (1 - 6) mm²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 10
TIGHTENING TORQUE	1.7 Nm, Screw terminals, Main cable

Bloki wyzwalaczy

OVERLOAD RELEASE CURRENT SETTING - MAX	6.3 A
OVERLOAD RELEASE CURRENT SETTING - MIN	4 A

Do pobrania	
CHARACTERISTIC CURVE	eaton-manual-motor-starters-characteristic-characteristic-curve-008.eps
DEKLARACJE ZGODNOŚCI	eaton-motor-protective-circuit-breaker-declaration-of-conformity-eu250692en.pdf eaton-motor-protective-circuit-breaker-declaration-of-conformity-uk251175en.pdf
INSTRUKCJE MONTAŻU	IL03407011Z.pdf IL122012ZU IL03402034Z
INSTRUKCJE OBSŁUGI	IL122023ZU
MODELE ECAD	ETN.278483.edz
MODELE MCAD	eaton-breakers-mcad-drawings-pkzm01.dwg DA-CS-pkzm01
RYSUNKI	eaton-manual-motor-starters-circuit-breaker-pkzm01-dimensions.eps eaton-manual-motor-starters-mounting-3d-drawing-002.eps eaton-manual-motor-starters-circuit-breaker-pkzm01-3d-drawing-002.eps eaton-general-ie-ready-dilm-contactor-standards.eps

NAZWA PROJEKTU:	
NUMER PROJEKTU:	
PRZYGOTOWANE PRZEZ:	
DATA:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2026 Eaton. Wszelkie prawa zastrzeżone.

Najnowsze informacje o produktach i wsparciu znajdują się na naszych mediach społecznościowych.