Specyfikacje



Zdjęcie jest reprezentatywne

Eaton 248393

Z-MS-1,0/2. Motor-Protective Circuit-Breakers, 0,63-1A, 2p

Specyfikacje ogólne	
PRODUCT NAME	Eaton Distribution parts
CATALOG NUMBER	248393
EAN	4015082483937
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	75 mm
PRODUCT WIDTH	36 mm
PRODUCT WEIGHT	0.244 kg
COMPLIANCES	RoHS conform
MODEL CODE	Z-MS-1,0/2

Powering Business Worldwide

Specyfikacje produktu

ACTUATOR TYPE	Rocker lever
SWITCH OFF TECHNIQUE	Magnetic
ADJUSTMENT RANGE SHORT-TERM DELAYED SHORT-CIRCUIT RELEASE - MIN	10 A
ADJUSTMENT RANGE UNDELAYED SHORT-CIRCUIT RELEASE - MAX	13 A
ADJUSTMENT RANGE UNDELAYED SHORT-CIRCUIT RELEASE - MIN	10 A
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	2.15 W
OVERLOAD RELEASE CURRENT SETTING - MAX	1 A
OVERLOAD RELEASE CURRENT SETTING - MIN	0.63 A
RATED OPERATING POWER AT AC-3, 400 V	0.25 kW
RATED OPERATING VOLTAGE (UE) - MAX	400 V
RATED OPERATING VOLTAGE (UE) - MIN	400 V
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	1 A
RATED SHORT-CIRCUIT BREAKING CAPACITY AT 400 V AC	10 kA
RATED UNINTERRUPTED CURRENT (IU)	1 A
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
FITTED WITH:	Thermal protection
DEGREE OF PROTECTION	IP20
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	4.3 W
DEVICE CONSTRUCTION	Complete device in housing
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
NUMBER OF POLES	Two-pole

Do pobrania

DEKLARACJE ZGODNOŚCI	eaton-distribution-parts-declaration-of-conformity-eu250440en.pdf
MODELE MCAD	eaton-adjustable-non-selective-universal-mcb-mcad-drawings-z-ms-2p.dwg eaton-adjustable-non-selective-universal-mcb-mcad-3d-models-z-ms-2p.stp
RYSUNKI	eaton-wiring-diagram-ms7-2p.jpg eaton-dimensions-mas-ms7.jpg eaton-3d-drawing-diagr-ms-40a.jpg

NAZWA PROJEKTU:	
NUMER PROJEKTU:	
PRZYGOTOWANE PRZEZ:	
DATA:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2026 Eaton. Wszelkie prawa zastrzeżone.

Najnowsze informacje o produktach i wsparciu znajdują się na naszych mediach społecznościowych.