# Specyfikacje

## Eaton 72896

Eaton motor control auxiliary contact, Standard, Operational: 500 Vac, 250 Vdc, With interlocking opposing contacts, For use with PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKE, 1N/O-1N/C, Screw terminal

| Specyfikacje ogólne | |
|---|---|
| **PRODUCT NAME** | Eaton motor control auxiliary contact |
| **CATALOG NUMBER** | 72896 |
| **UPC** | 786689716509 |
| **PRODUCT LENGTH/DEPTH** | 68 mm |
| **PRODUCT HEIGHT** | 90 mm |
| **PRODUCT WIDTH** | 9 mm |
| **PRODUCT WEIGHT** | 0.5 kg |
| **COMPLIANCES** | CE Marked |
| **CERTIFICATIONS** | CSA Certified<br>IEC Rated<br>UL Listed |

Powering Business Worldwide

## Specyfikacje produktu

| | |
|---|---|
| **USED WITH** | Interlocking opposing contacts |
| **APPLICATION** | For use with PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKE, 1N/O-1N/C, Screw terminal |
| **TYPE** | Renewal Parts/Accessories |
| **VOLTAGE RATING** | 500 Vac, 250 Vdc |
| **CONTACT CONFIGURATION** | 1 NO-1 NC |
| **TERMINALS** | Screw |

## Do pobrania

| | |
|---|---|
| **NAZWA PROJEKTU:** | |
| **NUMER PROJEKTU:** | |
| **PRZYGOTOWANE PRZEZ:** | |
| **DATA:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2026 Eaton. Wszelkie prawa zastrzeżone.

Najnowsze informacje o produktach i wsparciu znajdują się na naszych mediach społecznościowych.